

# LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Stephan J. Szyszkoski

Field Survey Date: December 13, 2017

For corner(s) in: Houghton County

## Original Public Land Survey Corner

## Corner Code

S          T          R           
S          T          R           
S          T          R           
S          T          R         

## Property Corner

## 1/16 Corner Code

a. S 10 T 51N R 36W 14 (GCDB 500520)  
a. S 11 T 51N R 36W 10 (GCDB 500520)  
b. S          T          R                    
b. S          T          R                  

|    | A | B  | C | D  | E | F  | G | H  | I | J  | K | L  | M |    |
|----|---|----|---|----|---|----|---|----|---|----|---|----|---|----|
| 1  |   |    |   |    |   |    |   |    |   |    |   |    |   | 1  |
| 2  |   | 6  |   | 5  |   | 4  |   | 3  |   | 2  |   | 1  |   | 2  |
| 3  |   |    |   |    |   |    |   |    |   |    |   |    |   | 3  |
| 4  |   | 7  |   | 8  |   | 9  |   | 10 |   | 11 |   | 12 |   | 4  |
| 5  |   |    |   |    |   |    |   |    |   |    |   |    |   | 5  |
| 6  |   | 18 |   | 17 |   | 16 |   | 15 |   | 14 |   | 13 |   | 6  |
| 7  |   |    |   |    |   |    |   |    |   |    |   |    |   | 7  |
| 8  |   | 19 |   | 20 |   | 21 |   | 22 |   | 23 |   | 24 |   | 8  |
| 9  |   |    |   |    |   |    |   |    |   |    |   |    |   | 9  |
| 10 |   | 30 |   | 29 |   | 28 |   | 27 |   | 26 |   | 25 |   | 10 |
| 11 |   |    |   |    |   |    |   |    |   |    |   |    |   | 11 |
| 12 |   | 31 |   | 32 |   | 33 |   | 34 |   | 35 |   | 36 |   | 12 |
| 13 |   |    |   |    |   |    |   |    |   |    |   |    |   | 13 |
|    | A | B  | C | D  | E | F  | G | H  | I | J  | K | L  | M |    |

## Part A. Corner History

a.) South 1/16 corner between Sections 10 and 11. Not previously monumented.

## Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

a.) Established the position for the corner midway and on a straight line between Quarter corner 1308.52' north and Section corner 1308.52' south.

## Part C: Field Evidence of Perpetuation or Monumentation of Corner

a. Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
6" Maple N06°W 25.6' mrkd "1/16S BT"  
5" Sugar East 9.95' do  
10" Hemlock S08°W 11.85' do  
7" Maple N57°W 24.6' do  
Set sq'd cedar post adjacent.  
E= 7859007.85 N= 228701.00



Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum.

Stephan J. Szyszkoski 01/10/2018