

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Houghton

(County)

Located In:

Corner Code #

1. Public Land Survey

T 51N R 36W

H2

T 51N R 36W

H3

T R

S T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Dec 04 2006

I, Stephan J. Szyszkoski, in a field survey on \_\_\_\_\_, 20\_\_\_\_ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(H2) Center of Section 3. Not established in the original survey.

(H3) Quarter corner common to Sections 3 and 10. 1848 - Established by S.W.Higgins, Deputy Surveyor: West corrected between Sections 3 and 10 ... 40.07 Set 1/4 Section post on true line. Sugar 12 N05W 19 links, Birch 18 S30E 03 links. ...80.14 Section corner.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(H2) Established the corner at the intersection of straight lines connecting opposite 1/4 corners.

(H3) The original post and accessories were not recovered. Found no acceptable evidence of the position of the original corner on the ground. Reestablished the corner position midway and on the Section line between monumented Section corners 2739.22' east and west, being proportionate to the original record.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(H2) Set 1"IDx54" I.pipe with 4" alum.

MDNR cap. Set measuring nails in:

8" Spruce N54E 46.6' mkrd "C1/4 BT"

12" Hemlock N60W 50.7' do

5" Hemlock N21W 25.4' do

7" Maple N03W 22.5' do

Set sq'd Balsam post adjacent. Bearings are magnetic. Distances are to nail with tag.

(H3) Set 1"IDx32" I.pipe with 4" alum.

MDNR cap. Set measuring nails in:

8" Sugar N53E 25.4' mkrd "1/4S NBT"

11" Sugar S29W 16.4' do

4" Sugar N88W 11.8' do

8" Sugar N04W 18.4' do

Set sq'd Cedar post adjacent. Bearings are magnetic. Distances are to nail with tag.



Signed by Stephan J. Szyszkoski  
Surveyor's Michigan License No. 33986

Date 1/18/07

For the Michigan Department of Natural Resources, Office of Land and Facilities