MICHIGAN DEPARTMENT OF CONSERVATION FORESTRY DIVISION

LAND CORNER RECORD

T_51 NR 36 W

		. Houghto	n	COUNT
OF COF	RNER <u>Section</u> cor	ner common to Sect	ions 10, 11, 1	and_15
OF COR	NER MONUMENT	l" Pipe with 4" Br	ass_Cap	
TO CORN	IER 18" White Pin	e <u>(S 15 NBT)</u> s	_63° W _ 101 L:	inks
	13" Hard Mapl	e (s 14 NBT) s	.47° E _ 59 Id	nks
	10" Hard Mapl	e	82° E _ 63 Li	nks
	OF COR	OF CORNER MONUMENT. TO CORNER 18" White Pin 13" Hard Mapl	OF CORNER Section corner common to Sect OF CORNER MONUMENT 1" Pipe with 4" Br. TO CORNER 18" White Pine (S 15 NBT) S	OF CORNER Section corner common to Sections 10, 11, 14 OF CORNER MONUMENT L. Pipe with 4. Brass Cap TO CORNER 18. White Pine (S 15 NBT) S 63° W 101 Line 13. Hard Maple (S 14 NBT) S 47° E 59 Line 10. Hard Maple (S 11 NBT) N 82° E 63 Line

DESCRIPTION IN DETAIL AS TO HOW CORNER WAS LOCATED AND IDENTIFIED OR

RESTORED. This corner was re-established by double proportionate measures from corners: 1/2 mile east 1/2 mile north

1 mile south 2 miles west

Position checks to streams north and east.

Corner was placed and witnessed October 9, 1959 with F. Bray and L. Stevens.

SURVEYORS SEAL

SIGNED _______ Suckles _____ DATE 2/25/60 _______ Billy D. Buckler