

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
 Noughton

Located In:

Corner Code #

1. Public Land Survey	T	52N	R	36W	06
	T	52N	R	36W	86
	T		R		
	T		R		
2. Property Controlling	S		T	R	
in Section	S		T	R	
3. Miscellaneous	S		T	R	
Property in Sec.	S		T	R	

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
 5. Private Claims _____

I, Stephan J. Szyszkoski, on 06 October 17, 1995,
 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
 in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
 current manual of survey instructions of the United States Department of the Interior, Bureau of Land
 Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
 Court of Law; established, re-established, monumented, re-monumented, recovered, found as
 expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
 on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

(06) Center of Section 17. Corner not established in the original survey. Found no subsequent record.
 (86) Center of Section 18. Corner not established in the original survey. Found no subsequent record.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(06) Found no evidence of prior monumentation at the corner position. Established the corner at the intersection of straight lines
 connecting opposite 1/4 corners. At the position for the corner, I placed a 1"IDx32" iron pipe capped with a 4" dia. cast aluminum
 MDNR tablet, appropriately stamped.
 (86) Found no evidence of prior monumentation at the corner position. Established the corner at the intersection of straight lines
 connecting opposite 1/4 corners. At the position for the corner, I placed a 1"IDx32" iron pipe capped with a 4" dia. cast aluminum
 MDNR tablet, appropriately stamped.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(06) Set 1" pipe with 4" MDNR cap. Blazed and scribed the following bearing trees:	(86) Set 1" pipe with 4" MDNR cap. Blazed and scribed the following bearing trees:
10" Ironwood N20E 24.6' "1/4S BT"	12" Sugar N46E 8.3' "1/4S BT"
10" Sugar S82E 27.9' "1/4S BT"	10" Sugar S49E 3.3' "1/4S BT"
12" Sugar S10W 30.3' "1/4S BT"	7" W. Birch S62W 39.7' "1/4S BT"
13" Sugar S82W 23.4' "1/4S BT"	11" Sugar N57W 21.6' "1/4S BT"
Bearings are magnetic. Placed a 3" squared sugar post adjacent.	Bearings are magnetic. Set a 3" squared sugar post adjacent.



Signed by Stephan J. Szyszkoski Date 10-26-95
 Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources - Forest Management Division