

LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Stephan J. Szyszkoski

Field Survey Date: November 7, 2017

For corner(s) in: Houghton County

Original Public Land Survey Corner

Corner Code

S T R
S T R
S T R
S T R

Property Corner

1/16 Corner Code

a. S 31 T 53N R 33W N.E. corner Gov't Lot 6
S T R
b. S 31 T 53N R 33W S.E. corner Gov't Lot 6
S T R

	A	B	C	D	E	F	G	H	I	J	K	L	M	
1														1
2	6			5		4		3		2		1		2
3														3
4	7			8		9		10		11		12		4
5														5
6	18			17		16		15		14		13		6
7														7
8	19			20		21		22		23		24		8
9														9
10	30			29		28		27		26		25		10
11														11
12	31			32		33		34		35		36		12
13														13
	A	B	C	D	E	F	G	H	I	J	K	L	M	

Part A. Corner History

a.) The NE corner of Gov't Lot 6 being the intersection of the E-W 1/4 line of Section 31 with the west (left) bank of the Sturgeon River. Not previously monumented.

b.) The SE corner of Gov't Lot 6 being the intersection of the South 1/16 line of Section 31 with the west (left) bank of the Sturgeon River. Not previously monumented.

Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

a.) Established the position for the corner on a straight line between the Center of Section and the East 1/4 corner of Section 31 at the apparent ordinary high water mark on the left bank of the Sturgeon River. The position was not monumented. Established a WITNESS CORNER 40.0' west of the corner position, on the 1/4 line. The W.C. is 1072.92' east of the monumented Center of Section.

b.) Established the position for the corner on a straight line between 1/16 corners #12 and #14 of Section 31 at the apparent ordinary high water mark on the left bank of the Sturgeon River. The position was not monumented. Established a WITNESS CORNER 50.0' west of the corner position, on the 1/4 line. The W.C. is 632.85' east of the Center-South 1/16 corner, Section 31

Part C: Field Evidence of Perpetuation or Monumentation of Corner

a.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap at the WITNESS CORNER.

Set measuring nail with MDNR tag in the side of:

21" Maple N12°E 13.75' mrkd "WC BT"

5" Maple N70°E 30.7' do

5" Sugar S23°W 29.4' do

7" Maple N27°W 4.9' do

Set sq'd cedar post adjacent.

E= 7882980.01 N= 241495.37 (the W.C.)

b.) Set 1"IDx28" I.pipe with plastic MDNR cap at the WITNESS CORNER.

Set measuring nail with MDNR tag in the side of:

7" Ash N08°E 15.1' mrkd "WC BT"

6" Balsam S88°E 4.95' do

13" Maple S03°W 8.25' do

15" Maple N74°W 16.4' do

Set sq'd cedar post adjacent.

E= 7882838.54 N= 241098.39 (the W.C.)

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum

Stephan J. Szyszkoski

01/11/2018

Professional Surveyor's License No.: 33986

page 1 of 1

Prepared By: S.J. Szyszkoski for the Michigan Dept. of Natural Resources, 427 N. US41 Baraga, MI 49908

