

LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Stephan J. Szyszkoski

Field Survey Date: November 8, 2017

For corner(s) in: Houghton County

Original Public Land Survey Corner

Corner Code

S T R
S T R
S T R
S T R

Property Corner

1/16 Corner Code

a. S 31 T 53N R 33W 12 (GCDB 140120)
b. S 31 T 53N R 33W 11 (GCDB 120120)
S T R
S T R

1	A	B	C	D	E	F	G	H	I	J	K	L	M	1
2		6		5		4		3		2		1		2
3														3
4		7		8		9		10		11		12		4
5														5
6		18		17		16		15		14		13		6
7														7
8		19		20		21		22		23		24		8
9														9
10		30		29		28		27		26		25		10
11														11
12		31		32		33		34		35		36		12
13														13
	A	B	C	D	E	F	G	H	I	J	K	L	M	

Part A: Corner History

a.) Center-South 1/16 corner, Section 31. Not previously monumented.

b.) Southwest 1/16 corner, Section 31. Not previously monumented.



Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

a.) Established the position for the corner midway and on a straight line between Quarter corner 1311.62' south and the Center of Section 31 1311.62' north.

b.) Established the position for the corner at the intersection of straight lines connecting opposite 1/16 corners, those to the east and west being monumented.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

a.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
14" Sugar N14°E 5.4' mrkd "1/16S BT"
10" Y.Birch S87°E 17.8' do
10" Y.Birch S22°W 2.0' do
7" Sugar S86°W 11.6' do
E= 7882645.69 N= 241101.69

b.) Set 1"IDx28" I.pipe with plastic MDNR cap.
Set measuring nail with MDNR tag in the side of:
4" Sugar N11°E 4.6' mrkd "1/16S BT"
9" Sugar S52°E 6.9' do
4" Sugar S08°E 6.4' do
5" Sugar N61°W 23.15' do
Set sq'd cedar post adjacent.
E= 7882242.41 N= 241108.91

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum.

Stephan J. Szyszkoski 01/11/2018