

# LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Stephan J. Szyszkoski

Field Survey Date: October 30, 2017

For corner(s) in: Houghton County

## Original Public Land Survey Corner

## Corner Code

a. S            T 53N R 33W  
 S            T        R         
 S            T        R         
 S            T        R       

B11 (GCDB 140200)

## Property Corner

## 1/16 Corner Code

b. S 31 T 53N R 33W  
 b. S 30 T 53N R 33W  
 S            T        R         
 S            T        R       

1 (GCDB 120200)

15 (GCDB 120200)

1	A	B	C	D	E	F	G	H	I	J	K	L	M	1
2	6			5		4		3		2		1		2
3														3
4	7			8		9		10		11		12		4
5														5
6	18			17		16		15		14		13		6
7														7
8	19			20		21		22		23		24		8
9														9
10	30			29		28		27		26		25		10
11	●	●												11
12	31			32		33		34		35		36		12
13														13
	A	B	C	D	E	F	G	H	I	J	K	L	M	

## Part A. Corner History

a.) Quarter corner common to Sections 30 and 31. 1845 - Established by Wm. Ives, Deputy Surveyor, for Douglas Houghton, midway and on the Section line between Section corners 40.00 chains east and west. Set post. Hemlock 15" S05°E 05 links, Sugar 16" N60°E 04 links. Found no subsequent record.

b.) West 1/16 corner between Sections 30 and 31. Not previously monumented.

## Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

a.) The original post and accessories were not recovered. Found no evidence of the position of the original corner on the ground. Reestablished the position for the corner midway and on the Section line between Section corners 2654.42' east and west.

b.) Established the position for the corner midway and on the Section line between Section corner 1327.21' west and Quarter corner 1327.21' east.

## Part C: Field Evidence of Perpetuation or Monumentation of Corner

a.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
 Set measuring nail with MDNR tag in the side of:  
 9" Sugar S64°E 17.9' mrkd "1/4S NBT"  
 12" Sugar S38°W 15.3' do  
 5" Sugar S70°W 7.8' do  
 14" Sugar N36°W 33.4' do  
 Set sq'd cedar post adjacent.  
 E= 7882667.81 N= 242301.22

b.) Set 1"IDx28" I.pipe with plastic MDNR cap.  
 Set measuring nail with MDNR tag in the side of:  
 18" Maple N08°E 2.1' mrkd "1/16S BT"  
 6" Sugar S43°E 7.0' do  
 5" Hemlock S16°W 15.0' do  
 Maple S62°W 9.95'  
 Squared a 2" maple for post S55E 1.2'  
 E= 7882263.39 N= 242309.95

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00

Stephan J. Szyszkoski

01/11/2018

Professional Surveyor's License No.: 33986

page 1 of 1

Prepared By: S.J. Szyszkoski for the Michigan Dept. of Natural Resources, 427 N. US41 Baraga, MI 49908

