

LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Stephan J. Szyszkoski

Field Survey Date: May 18, 2016

For corner(s) in: Houghton County

Original Public Land Survey Corner

Corner Code

a. S T 53N R 34W C10 (GCDB 200240)
 S T R
 S T R
 S T R

Property Corner

1/16 Corner Code

b. S 19 T 53N R 34W 7 (GCDB 200360)
 b. S 20 T 53N R 34W 3 (GCDB 200360)
 S T R
 S T R

1	A	B	C	D	E	F	G	H	I	J	K	L	M	1
2		6		5		4		3		2		1		2
3														3
4		7		8		9		10		11		12		4
5														5
6		18		17		16		15		14		13		6
7														7
8		19	●	20		21		22		23		24		8
9														9
10		30	●	29		28		27		26		25		10
11														11
12		31		32		33		34		35		36		12
13														13
	A	B	C	D	E	F	G	H	I	J	K	L	M	

Part A. Corner History

a.) Quarter corner common to Sections 29 and 30. 1846 - Deputy S.W.Higgins established the corner midway and on line between Section corners 40.00 chains north and south. Set Post. Spruce 12" N50°W 20 links, Cedar 12" S40°E 35 links. Circa 1920 - P.A.Larsen, forester and surveyor, noted "no trace" of the original corner. Found no subsequent record.

b.) North 1/16 corner between Sections 19 and 20. Not previously monumented.

Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

a.) The original post and accessories were not recovered. Found no evidence of the position of the original corner on the ground. Reestablished the position for the corner midway and on the Section line between Section corners 2549.39' north and south.

b.) Established the position for the corner midway and on the Section line between Section corner 1421.49' north and Quarter corner 1421.49' south.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

(a.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
 Set measuring nail with MDNR tag in the side of:
 10" Cedar N73°E 36.9' mrkd "1/4S NBT"
 9" Cedar N80°E 30.65' do
 11" Cedar S28°W 33.6' do
 12" Cedar N03°W 20.6' do
 Set sq'd cedar post adjacent.
 E= 7873839.777 N= 243216.368

(b.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
 Set measuring nail with MDNR tag in the side of:
 10" Cedar S12°E 4.15' mrkd "1/16S BT"
 10" Cedar S40°W 5.25' do
 7" Balsam S74°W 17.1' do
 10" W.Spruce N50°W 19.65' do
 Set sq'd cedar post adjacent.
 E= 7873893.625 N= 245240.626

Bearings are magnetic. Coordinates are MCS83, NAD83(2011) Epoch 2010.00, in meters.
 Coordinate Reference: NGS PID DL5986, E= 7882233.252 m. N= 259878.551 m.

Stephan J. Szyszkoski

06/29/2016

Professional Surveyor's License No.: 33986

page 1 of 1

Prepared By: S.J. Szyszkoski for the Michigan Dept. of Natural Resources, 427 N. US41 Baraga, MI 49908

