LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Houghton (County)	_ Located In:	Corner Code #										
1. Public Land Survey	T 53N R 35W	I12 (GCDB 500140)										
 Property Controlling in Section Miscellaneous Property in Sec. 	T R S T R S											
4. Lot No. , Red 5. Private Claims 1, Stephan J. Szyszkoski , ir	corded Plat	/28/15 do hereby state	1 A 2 - 3 -		c D	E E		np &	File	J I		L M
that under requirements of P.A. above were in conformance with a instructions of the United States if a Court of Law and /or that the court of Law and /or the court of Law	74, Michigan P.A. of 1970, the corner pregulations and rules therefore as require Department of the Interior, Bureau of Lacorner points mentioned in lines 3, 4 and d of Land Surveyors or by a Decree	points mentioned in lines 1 and 2 ed in the current manual of survey and Management or by a decree of 5 above were in conformance with	8 -	19	17 		16-21-	1 1 1 2	5	 14-	—1 —1 —2	3-
on this certificate.	ers, all in the same town and range,		9 10 11 12 12 13	31—	32		33	3	7	26— 1 1 15— 1	3	5
A. Description of original m	onument and accessories and/or s	subsequent restoration:										

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(I12) The original post and accessories were not recovered. Found and accepted a local corner position well marked by blazed trees, a USFS location poster dating to 1954, and a 14" Cedar tree with face blazes at right angles, 5.6' distant, dated to 1952, presumably the angle pointing to the corner. The position is substantially at record distance from I11 (2646.42' M), leaving the 1/2 mile to I13 2.93 chains short of record (2446.76' M). Determined the position on the ground which gave the best fit to the face blazes and markings and monumented that position. After monumenting the position and completing my survey, I discovered a MEAD CORP. forester's record stating that the corner was marked by a cedar post, of which no trace was found in the field. Their record states that there is a yellow tag on a 12" Cedar Due East 5'. I suspect that the record Cedar is the same tree as aforementioned but there is no tag present. The bearing and distance to this tree suggests that the MEAD position was about 3 ft. south of the position monumented. Since the MEAD corner does not purport to be a perpetuation of the original position and it does not appear to have been relied upon to any great extent, and further does not conform to the right angle blazing on the Cedar tree, which appears to have been intended as a marking that points toward the corner, I concluded that the position monumented was a reasonable and satisfactory reestablishment of the position of the corner.

(I12) Quarter corner common to Sections 34 and 35. 1846 - Established by S.W.Higgins, Deputy, midway and on the Section line between Section corners 40.00 ch. North and South. Set post in

Y.Birch 12" N77°W 8 links, Spruce 9" N54°E 13 links. See additional information below.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(I12) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 13" Cedar N49°E 21.7' mrkd "1/4S NBT" 14" Cedar S60°E 6.15' w/old blazes do 7" Hemlock S39°W 6.25' do 5" Balsam N87°W 25.7' do Set sq'd cedar post adjacent. E= 7868972.594 N= 241731.063



Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum. Coord. Ref.=NGS PID D08499: N= 221257.624 m. E= 7884435.169 m.

Signed by Steshen market	eli.	Date	11/04/2015	
Surveyor's Michigan License No.	33986			