

JAN 19 2001

SECTION

Re-Monumented 2, Page 1/15

2000 REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For Corners in VERONA Township

Huron  
(County)

Located in:

Corner Code #

STATE OF MICHIGAN  
HURON COUNTY  
RECORDED

8 DEC 2000 9:59 AM

FRANCES L. HOLDWICK  
REGISTER OF DEEDS

1. Public Land Survey

T 16N R 13E A - 2

2. Property Controlling S  
in Section S

T R

3. Miscellaneous S  
Property in Sec. S

T R

T R

T R

T R

T R

Register of Deeds Stamp & File Number


4. Lot No. , Recorded Plat

5. Private Claims

I, Russell L. Brown, in a field survey on August 4, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4, and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:  
1834 GLO H. Parke D.S. Set quarter section post, E. side Sec. 1, T16N-R12E  
Maple 20 S.15W 24; Cedar 9 N33W 21  
COUNTY SURVEYOR RECORD: None  
COUNTY ROAD COMMISSION RECORD: None  
L.C.R.C.: None  
RECORDED SURVEYS: Continued next page  
UNRECORDED SURVEYS: None



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No evidence of original corner or accessories found.

Set 1/2" x 18" Steel Stake in Monument Box.

Accepted set 1/2" x 18" Steel Stake in Monument Box as best evidence of original corner position.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A - 2, W. 1/4 Cor. Sec. 6, T16N-R13E

Set 1/2" x 18" Steel Stake in Monument Box

WITNESSES:

N70°E 58.60' to Notch in N. End 24" C.M.P.

S80°E 51.95' to Notch in S. End 24" C.M.P.

West 51.95' to Northerly point of fence post in center of 12" concrete corner Post

S30°E 53.85' to 1/2" Dia. Re-Rod Set

South 2614.40' to A-3, S.W. Cor. Sec. 6 and N.W. Cor. Sec. 7, T16N-R13E

North 2517.37' to A-1, Corner Common to T16N-R12E, T16N-R13E, T17N-R12E and T17N-R13E

NOTE:

This corner is common with  
M - 2, T16N-R12E

Signed by Russell L. Brown  
Surveyor's Michigan License No. 24588

Date Nov. 2, 2000

Peer group approved at meeting held November 2, 2000. RLB

JAN 19 2001

SECTION

*Re-Mon Liber 2, Page 115*

2000 REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in VERONA Township,  
Huron County, T16N-R13E  
A-2 Continued

RECORDED SURVEYS:

5-31-78, Case Surveying, Stewart G. Case P.S., Liber 3 survey, page 410 of Huron County Records.  
W. ¼ Cor. Frac. Sec. 6, T16N-R13E

P.K. Nail in place

WITNESSES:

N.W. Cor. N. Headwall, N65°E 65.67'

S.W. Cor. S. Headwall, 49.40'

Center 1 foot round concrete Corner Post, West 47.5'

3-28-79, Case Surveying, Stewart G. Case P.S. 15399, Liber 3 survey, page 715 of Huron County Records.  
East ¼ Corner Fractional Section 1, T16N-R12E

P.K. Nail in place over corner

WITNESSES:

Same as Liber 3 survey, page 410 of Huron County Records

3-28-79, Case Surveying, Stewart G. Case P.S. 15399, Liber 3 survey, page 760 of Huron County Records  
East ¼ Corner Fractional Section 1, T16N-R12E

No object stated

WITNESSES:

Same as Liber 3 survey, page 410 of Huron County Records.

