

JAN 19 2001

SECTION

Re-Mon Liber 2, Page 121

2000 REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For Corners in VERONA Township

Huron  
(County)

Located in:

Corner Code #

1. Public Land Survey

T 16N R 13E A - 10

2. Property Controlling S  
in Section S

T R

T R

T R

T R

3. Miscellaneous S  
Property in Sec. S

T R

T R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

STATE OF MICHIGAN  
HURON COUNTY  
RECORDED

8 DEC 2000 10:00 AM

FRANCES L. HOLDWICK  
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

I, Russell L. Brown, in a field survey on June 23, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4, and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1834 GLO H. Parke D.S. Set quarter Section post E. Side Section 25, 16N-R12E

Birch 10 S23W 28, Cedar 5 N2 1/2W 19

COUNTY SURVEYOR RECORD: None

COUNTY ROAD COMMISSION RECORD: Iron Pin, WITNESSES: Spike T.P. N70°E 86.5'; N.W. Cor. Wall S50E 100.6'

L.C.R.C.: None

RECORDED SURVEYS: Continued next page


UNRECORDED SURVEY: Continued next page

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No evidence of original corner or accessories found.

Found 3/4" Dia. Re-Rod in Monument Box.

Accepted Found 3/4" Dia. Re-Rod as best evidence of original corner position



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A - 10, W. 1/4 Corner Section 30, T16N-R13E

Found 3/4" Dia. Re-Rod in Monument Box

WITNESSES:

N45°E 79.34' to Spike in N.W. Cor. of West Sign Post

S45°E 61.98' to Spike in S.E. Face of Power Pole

S20°E 153.50' to Spike in W. Face of Power Pole

S45°W 54.38' to Notch in W. End 18" C.M.P.

South 2619.50' A-11 S.W. Cor. Sec. 30, T16N-R13E

North 2652.08' A-9 N.W. Cor. Sec. 30, T16N-R13E

NOTE:

This corner is common with  
M - 10, T16N-R12E

Signed by Russell L. Brown  
Surveyor's Michigan License No. 24588

Date Nov. 2, 2000

Peer group approved at meeting held November 2, 2000. RLB

JAN 19 2001

SECTION

*Re Mon Liber 2, Page 121 A*

2000 REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in VERONA Township

Huron County, T16N-R13E  
A-10 Continued

RECORDED SURVEYS:

2-22-73, Case Surveying, Stewart G. Case P.S. 15399, Liber 1 Survey, Page 413 of Huron County Records.  
W. ¼ Cor. Frac. Sec. 30, T16N-R13E Verona Township

Found Monument Box in Place

WITNESSES:

Spike on N.E. Side of Power Pole, S60°E 62.0'  
Spike on S. Side of Telephone Pole, S80°W 40.32'  
Spike on S.E. Side of Guard Post, S30°W 47.55'

6-8-76, Case Surveying, Stewart G. Case P.S. 15399, Liber 2 Survey, Page 645 of Huron County Records.  
W. ¼ Cor. Frac. Sec. 30, T16N-R13E, Verona Township  
Same object and witnesses as Liber 1 Survey, Page 413 of Huron County Records.

4-20-78, Case Surveying, Stewart G. Case P.S. 15399, Liber 3 Survey, Page 407 of Huron County Records.  
W. ¼ Cor. Frac. Sec. 30, T16N-R13E, Verona Township  
Same object and witnesses as Liber 1 Survey, Page 413 of Huron County Records.

4-20-78, Case Surveying, Stewart G. Case P.S. 15399, Liber 3 Survey, Page 414 of Huron County Records.  
W. ¼ Cor. Frac. Sec. 30, T16N-R13E, Verona Township  
Same object and witnesses as Liber 1 Survey, Page 413 of Huron County Records.

5-3-78, Case Surveying, Stewart G. Case P.S. 15399, Liber 3 Survey, Page 559 of Huron County Records.  
W. ¼ Cor. Frac. Sec. 30, T16N-R13E, Verona Township  
Same object and witnesses as Liber 1 Survey, Page 413 of Huron County Records.

2-28-79, Case Surveying, Stewart G. Case P.S. 15399, Liber 3 Survey, Page 720 of Huron County Records.  
W. ¼ Cor. Frac. Sec. 30, T16N-R13E, Verona Township  
Same object and witnesses as Liber 1 Survey, Page 413 of Huron County Records.

12-5-79, Case Surveying, Stewart G. Case P.S. 15399, Liber 4 Survey, Page 239 of Huron County Records.  
W. ¼ Cor. Frac. Sec. 30, T16N-R13E, Verona Township  
Same object and witnesses as Liber 1 Survey, Page 413 of Huron County Records.

UNRECORDED SURVEYS:

4-26-85, Huron Surveying, Inc., Russell L. Brown P.S. 24588,  
E. ¼ Cor. Sec. 25, T16N-R12E  
Found Iron in Monument Box

WITNESSES:

S45°E 62.0' to Spike in N.E. Side of Power Pole  
S40°W 53.0' to Center S.E. End 12" C.M.P.  
N45°E to spike in N.W. Cor. of 4" x 4" Wood Post, West Leg of Sign.

