

JAN 19 2001

SECTION

2000 REMONUMENTATION

Re-Monumented, Page 69

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Huron

(County)

Located in:

Corner Code #

1. Public Land Survey Sand Beach T16N R16E A-7
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

STATE OF MICHIGAN
HURON COUNTY
RECORDED

20 SEP 2000 2:04 PM

FRANCES L. HOLDWICK
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, Charles S. Getz, in a field survey on July 18, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

1	A	B	C	D	E	F	G	H	I	J	K	L
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	16		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

A. Description of original monument and accessories and/or subsequent restoration:

A-7 1834 G.L.O., H. Parke D.S. County Road Commission Records - 1"x4" Board

Set Post

Hemlock 14", S14°W, 6 1/2 Links

Birch 9", N22 1/2°W, 34 1/2 Links

Recorded Surveys - Kay, 12-15-76, Liber 3, Page 144, 3/4" Bar
Brown, 3-10-81, Liber 4, Page 584, 3/4" Steel Bar

L.C.R.C. - NONE

Unrecorded Surveys - Scott, 8-16-50, Certificate shows Corner Case, 2-8-71, Certificate shows Corner Brown, 6-8-93, 3/4" Bar

County Surveyor Records - C B Cottrell,
April 2, 1865, & May 11, 1865
3 Surveys refer to Corner

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-7

SW Cor, Section 18, T16N-R16E

Found 3/4" Bar, 1-1/2' Deep, Raised with 1/2" Re-Rod (Capped, #25859)

Accepted as the best available evidence

of the original corner position

(On Jenks Road)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-7

SW Cor, Section 18, T16N-R16E

Set 1/2" Re-Rod (Capped), over 3/4" Bar


N30°W 15.95' to a Reference Iron

N45°E 19.97' to a Reference Iron

S20°W 16.83' to a Reference Iron

South 2622.77' to W 1/4 Cor, Sec 19, T16N-R16E

North 2629.36' to W 1/4 Cor, Sec 18, T16N-R16E



Signed by

Charles S. Getz

Date July 23, 2000

Surveyor's Michigan License No. 25843

PEER GROUP APPROVED AT MEETING

HELD September 18, 2000. RLB