## DEC 1 2 1997

COMMISSION	LAND CORNER RECORDATION CERTIFICATE		9 Page	182
For corners in	Fining Requirement of Act 14, wich. F.A. 131	· ·		
INGHAM	Located In: Corner Code #	FI	LED	
(County)	ALAIEDON TOWNSHIP	DÇ.	022437	
1. Public Land Survey	T3N_R1WL-4	06/20/19	197 15:33:40 R OF DEEDS	
	T R	Paula	Johnson COUNTY, NI	k File Numbi
		A B C D	E F G H	I J K I
4. Lot No, Recorded Plat		2 - 6 - 5 -	3-	
5. Private Claims		3		
		4 7 8	910	-110
I, RON HELSEL , in a field survey on APRIL 29 , 19 97 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law;		5	21 - 22	23 -24
established, re-established, monument	ted, re-monumented, recovered, found as expressed	10 30 29	28 - 27-	26-7-25
below:		11 31 32	33-34-	353£
NOTE: Not more that 4 corners, all in to on this certificate.	he same town and range, may be recorded	13		
CORNER NOT SET IN ORIGINA  1) VOL. 2, PAGE 153, JAN. 10-11,  44 3/4 LINKS; SUGAR 8", N54E, 2  2) A L.C.R.C. WAS RECORDED IN L  EVIDENCE OF MONUMENT OR ACCES  OF OLD FENCES NORTH, SOUTH, EA  NAIL AND TAG IN NO  NAIL AND TAG IN N.	1878, COUNTY SURVEYOR, A.P. DRAKE CALLED FO	R. LESTER NO. 1 EEL POST IN CON TION LOCATION :	8998. * FOU ICRETE AT II	ND NO NTERSECTION
FOUND 2" PIPE IN CONCRETE AT EAST AND WEST. COMPUTATIONS	ORNER ORNER ORNER	RSECTION OF FE YS FOUND THIS	CORNER TO	BE 2.1 FEET
SET 3/4" X 24" FORM PIN ANI FOUND NAIL & TAG NO. 39100 S FOUND NAIL & TAG NO. 39100 S FOUND NAIL & TAG NO. 39100 E	ner and accessories established to perpetuate locating D CAP LABELED P. A. 345, P.S. NO. 18994 IN 2" PIP W/SIDE 6" ASH, AZ. 192 DEG. 18.67 FEET // SIDE 24" MAPLE, AZ. 103 DEG. 20.69 FEET // SIDE 8" ASH, AZ. 360 DEG. 7.96 FEET IE/SIDE 20" BASSWOOD, AZ. 283 DEG. 33.86 FEET DE 8" ASH, AZ. 24.21 FEET	E AT P.I. OF FENC	RON	
		***************************************	ELAEL TOD LYOR No. 8994	* * 10 * *
		THE WAY	A H D LANGE	•
Signed by Signed by	Date 6-	7-97	· · · · · · · · · · · · · · · · · · ·	
Surveyor's Michigan License No	18994 Liber 3 p	age 103		
	D A 345 INGHAM COUNTY	d by Michigan State Bo		/Eyors, Jan. 28, 197 Evised May 14,1976 Revised Jan., 198

P.A. 345 INGHAM COUNTY

## CONTINUED

- 3) SURVEYS WERE RECORDED IN LIBER 2, PAGES 939-943, DATED JULY 26, 1976, IN LIBER 2, PAGES 1050-1053, DATED NOV. 24, 1976, II LIBER 3, PAGES 44-45, DATED APRIL 22, 1977, AND IN LIBER 3, PAGES 343-345, DATED MAY 5, 1978, BY R. LESTER. HE CALLED FOR AND WITNESSED THE CORNER SAME AS 2-A ABOVE.
- A SURVEY WAS RECORDED IN LIBER 5, PAGES 411-412, DATED SEPT. 4, 1984, BY D. RICHARDSON NO. 31603, LIBER 3, PAGE 610 WA CITED FOR CORNER.
- A SURVEY WAS RECORDED IN LIBER 7, PAGES 681-683, DATED NOV. 8, 1995 BY T. WIEGMAN NO. 39100. "FND. 4" ANCHOR POST IN CONCRETE @ INTERSECTION FENCES E, W & S\*

FND. N & T (18998) N. SIDE LEANING 4" MAPLE, N74W, 17.2' (REC. 16.30') (FOUND) SET N & T SE SIDE 12" ASH, S57W, 18.65' (FOUND)

SET N & T NE SIDE 24" BASSWOOD, N40W, 33.70" (FOUND)

RESET N & T SW SIDE 24" MAPLE, S62E, 20.69' (FOUND)

SET N & T E SIDE 8" ELM, NORTH, 8.07" (FOUND)

36753-1937-15133110 82010151-15-15EEBC 994-1556650 1868-0-1008117,81 11.0055172