

SURVEY & REMONUMENTATION

OCT 11 1994

REMONUMENTATION CORNER
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in COMMISSION

Ionia (County) Located In: Corner Code ##
1. Public Land Survey T 6 N R 7 W K-1
T _____ R _____
T _____ R _____
T _____ R _____
2. Property Controlling S _____ T _____ R _____
in Section S _____ T _____ R _____
3. Miscellaneous S _____ T _____ R _____
Property in Sec. S _____ T _____ R _____
4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

STATE OF MICHIGAN
IONIA COUNTY
RECEIVED FOR RECORD
94 JUN -6 P 3:52
Diane M. DeLuca
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

I, Marinus Mulder, in a field survey on September 22, 1993, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

This corner was first established by U.S. Deputy Surveyor, John Mullett in 1830. This closing corner was a wood post 5.28 feet West of the standard corner for T7N-R7W witnessed by a 18" White Oak S 12° E 19 links and a 6" White Oak S 47° W 60 links. There is no recorded County Survey information

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Excavated gravel road bed opposite occupation line to the West and found a pile of stones. Did not find the standard corner. The distance from K-1 to the North 1/4 corner of Section 1 and the North 1/4 corner of Section 2 measures good, being 2651.40 to the West and 2654.58 to the East. Accepted the stone as the corner.

Ratified by Peer Group
P.A. 345 Ionia County

Date 4-20-94 m.a.m.
Marinus A. Mulder, Chairman

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 3/4" x 24" steel bar with a 2 3/4" diameter cap stamped "P.S. 25863" in the center of the stone pile.

Witnessed by:

Nail & tag Southeast side 16" quad Oak S 46° W 47.69'

Nail & tag Southwest side 12" Oak S 23° E 39.92'

Nail & tag North side 12" Pin Cherry S 82° E 20.92'

Nail & tag North side wood post S 84° W 32.11'

Southwest corner Section 36, T7N-R7W East 5.28' (3/4" x 24" steel bar with 2 3/4" diameter cap stamped P.S. 25863)

Signed by Marinus A. Mulder Date 4-21-94
Surveyor's Michigan License No. 25863