

SURVEY & REMONUMENTATION

FEB 21 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

COMMENCING YEAR 2000
RECEIVED FOR RECORD
IRON COUNTY, MICHIGAN

00 DEC -5 PM 12: 49

L. C. Records: L. 8, P. 194

Robert A. Goodreau
REGISTERED PROFESSIONAL SURVEYOR

For corners in

<u>Iron</u>	Located In:	Corner Code #
(County)		
1. Public Land Survey	T 42N R 31W	A-2 ✓
	T 42N R 32W	M-2
	T R	
	T R	
2. Property Controlling	S T R	
in Section	S T R	
3. Miscellaneous	S T R	
Property in Sec.	S T R	

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Robert A. Goodreau in a field survey on March 20, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

A-2/M-2 Original corner established by William Burt, U.S. Deputy Surveyor, on 31 July 1846

Original corner: Yellow pine post

Original witnesses: Y. pine 8 S53W 8 links
S. pine 12 N14E 25 links

1" ID iron pipe w/ 4" aluminum cap set by Arthur O. Enger, by proportionate measurement, on 2 May 1972 (Liber 1, Pages 107-108).

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-2/M-2 Found corner as described by Enger.

No witnesses found.

Corner record research on file with county representative.

PEER GROUP APPROVED

Iron Aug. 1, 2000
COUNTY REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-2/M-2 Accepted corner as found.

Witnesses: 16d nail in E. face 5" J. Pine N 34° W, 9.22'
16d nail in E. face 5" J. Pine N 31° E, 32.11'
16d nail in W. face 5" J. Pine S 24° E, 42.80'
16d nail in NW face 3" J. Pine N 32° W, 10.81'
sign post 1' North

Signed by *R. A. Goodreau*
Surveyor's Michigan License No. 43053

Date July 1, 2000

