

SURVEY & REMONUMENTATION

FEB 21 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

COMMENCING YEAR 2000
RECEIVED FOR RECORD
IRON COUNTY, MICHIGAN

00 DEC -5 PM 12:49

L.C. Records: L. 8, P. 198

REGISTERED BY 68006

For corners in

Iron (County)	Located in:	Corner Code #
1. Public Land Survey	T 42N R 31W	D-5
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Robert A. Goodreau in a field survey on March 22, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

A. Description of original monument and accessories and/or subsequent restoration:

D-5 Original corner established by John Burt, U.S. Deputy Surveyor, on 7 August 1849.

Original witnesses: Y. Pine 26 N42E 7 links
W. Pine 24 S44W 27 links.

1" ID iron pipe w/ 4" aluminum cap set by Keith L. Sackett RLS, using original bearing tree stumps, on 4 September 1985 (Liber 5, Page 109).

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D-5 Found corner as described by Sackett.

Found witnesses recorded by Sackett as:

7" Spruce	N68E	21.3 ft.	1/4S, NBT
6" Sugar	N73W	19.4 ft.	1/4S, NBT
6" Spruce	S63E	33.2 ft.	1/4S, NBT

PEER GROUP APPROVED

Iron Surveyors Assoc 11-14-2000

COUNTY REPRESENTATIVE

Corner record research on file with county representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-5 Accepted corner as found.

Witnesses: Set 16d nails in above bearing trees at recorded distances.
16d nail in W. face 5" Sugar Maple S 16° W 25.80'
Sign post North 1'

Signed by RA. GHL
Surveyor's Michigan License No. 43053

Date July 1, 2000

