

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 13 T 42N R 32W	12
	S T R	(GCDB 640420)
	S 13 T 42N R 32W	16
	S T R	(GCDB 660400)
	S T R	
3. Miscellaneous Property in Sec.		
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on 01/13/15 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(12-Sec. 13) Center-South 1/16 corner, Section 13. Not previously monumented.

(16-Sec. 13) East 1/16 corner between Sections 13 and 24. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(12-Sec. 13) Established the corner midway and on a straight line between Quarter corner 1317.32'
south and the Center of Section 13 1317.32' north.

(16-Sec. 13) Established the position for the corner midway and on the Section line between Quarter
corner 1315.94' west and Section corner 1315.94' east.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(12) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
5" Balsam N36°E 5.8' mrkd "1/16S BT"
6" Maple S65°E 18.2' do
6" W.Birch S57°W 13.7' do
7" Maple N76°W 8.9' do
Set sq'd cedar post adjacent.
E= 7903036.659 N= 139648.315

(16) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
5" Maple N74°E 14.85' mrkd "1/16S BT"
4" Maple S17°E 18.1' do
4" Maple S80°W 8.4' do
3" Maple N02°W 12.0' do
Set sq'd cedar post adjacent.
E= 7903433.112 N= 139238.631

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum)
Coord. Ref.=NGS PID AA8081: N= 147176.690 m. E= 7895147.466 m.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 02/11/2015

For the Michigan Department of Natural Resources, Forest Resources Division

