

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 13 T 42N R 32W	9
	S T R	(GCDB 660440)
	S 13 T 42N R 32W	13
	S T R	(GCDB 660420)
	S T R	
3. Miscellaneous Property in Sec.		
4. Lot No. , Recorded Plat		
5. Private Claims		

I, Stephan J. Szyszkoski, in a field survey on 13 01/12/15  
9 12/22/14 do hereby state  
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2  
above were in conformance with regulations and rules therefore as required in the current manual of survey  
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of  
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with  
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,  
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(9-Sec. 13) Center-East 1/16 corner, Section 13. Not previously monumented.

(13-Sec. 13) Southeast 1/16 corner, Section 13. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(9-Sec. 13) Established the position for the corner midway and on a straight line between Quarter  
corner 1318.63' east and the Center of Section 13 1318.63' west.

(13-Sec. 13) Established the position for the corner at the intersection of straight lines  
connecting opposite 1/16 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(9) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
10" J.Pine N29°E 42.0' mrkd "1/16S BT"  
4" R.Pine S68°E 25.9' do  
12" R.Pine S52°W 23.0' do  
5" J.Pine N18°W 36.5' do  
Set sq'd cedar post adjacent.  
E= 7903442.934 N= 140041.994

(13) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
5" W.Pine N56°E 39.8' mrkd "1/16S BT"  
3" Oak S04°E 28.1' do  
5" R.Pine S39°W 29.4' do  
7" J.Pine N21°W 44.7' do  
Set sq'd cedar post adjacent.  
E= 7903438.011 N= 139640.290

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum).  
Coord. Ref.=NGS PID AA8081: N= 147176.690 m. E= 7895147.466 m.

Signed by Stephan J. Szyszkoski Date 02/11/2015  
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

