

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
 Iron

(County)	Located In:	Corner Code #
1. Public Land Survey	T 42N R 32W	M13
	T 42N R 32W	G12
	T R	
	T R	
2. Property Controlling in Section	S 34 T 42N R 32W	12
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
 5. Private Claims _____

I, Stephan J. Szyszkoski, in a field survey on February 24, 1994, 19_____, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	16	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

- (M13) Quarter corner common to Section 34, T42N-R32W, and Section 3 T41N-R32W. Corner previously reestablished in 1971 by Arthur O. Enger, RLS by single proportionate measurement to the original record between section corners 1/2 mile east and west. Corner position perpetuated as follows: Set 1" I.D. x 3/8" iron pipe with 4" aluminum cap and NBTs - 10' W. Birch S59W 26.0', 8' W. Birch S31E 5.8'. Found no subsequent record.
- (G12) Quarter corner common to Sections 33-34. Corner previously reestablished in 1971 by Arthur O. Enger, RLS by single proportionate measurement to the original record between Section corners 1/2 mile North and South. Placed a 1" I.D. x 3/8" iron pipe with a 4" aluminum cap at the corner and marked the following NBTs: 6" Red Oak N89E 4.0', 6" Red Oak S20E 44.7', 6" squared Red Oak S78E 1.3'. Found no subsequent record.
- (12-Sec. 34) South 1/16 corner of Section 34. Corner not established in the original survey. Found no subsequent record.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- (M13) Found and accepted the monument as described above, in good condition, and at record bearing and distance from the 1971 bearing trees. Both NBTs are in good condition. Marked two new witnesses as described below.
- (G12) Found and accepted the monument as described above, in good condition, and at record bearing and distance from the three 1971 witnesses, all in good condition. Marked two new witnesses as described below.
- (12-Sec. 34) Found no evidence of prior monumentation at the corner position. Established the corner midway and on a straight line between quarter corner 1322.26' south and Center of Section 1322.26' north. At the position for the corner, I placed a 1" I.D. x 3/8" iron pipe capped with a 4" dia. cast aluminum MDNR tablet, appropriately stamped, and projecting about 15". From the corner position, a N-S wire fence is 19' East, and a fence corner post, with wire extending west and south, is 144.5' North and 19.0' West.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- | | | |
|---|--|---|
| (M13) Found 1" pipe with 4" MDNR cap. Blazed and scribed the following new bearing trees:
6" Spruce N86E 21.0' 1/4S NBT'
18" W. Pine N27E 39.8' 1/4S NBT'
Bearings are magnetic. | (G12) Found 1" pipe with 4" MDNR cap. Blazed and scribed the following new bearing trees:
10" W. Pine N67W 51.5' 1/4S NBT'
6" R. Pine S50W 56.2' 1/4S NBT'
Bearings are magnetic. | (12) Set a 1" pipe with 4" MDNR cap. Blazed and scribed the following bearing trees:
7" Spruce S38W 53.7' 1/16S BT'
5" Spruce N68W 46.6' 1/16S BT'
6" Oak S88W 81.0' 1/16S BT'
6" Spruce N71E 17.0' 1/16S BT'
Bearings are magnetic. |
|---|--|---|



Stephan J. Szyszkoski

Date 3-7-94