

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 11 T 42N R 36W	9
	S T R	(GCDB 560540)
	S 11 T 42N R 36W	2
	S T R	(GCDB 560600)
	S T R	
3. Miscellaneous Property in Sec.		
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on 04/23/15 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(9-Sec. 11) Center-East 1/16 corner, Section 11. Not previously monumented.

(2-Sec. 11) The 1/16 corner common to Sections 2 and 11, being the NE corner of Government Lot 1, Section 11. Not previously monumented.



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(9-Sec. 11) Established the position for the corner at the intersection of the E-W 1/4 line with the East 1/16 line. The direction of the E-W 1/4 line is the weighted mean bearing of the north line of the Section and that part of the south line of the Section lying east of Bass Lake. The East 1/16 line is parallel with the north 1/2 mile of the east line of Sec. 11.

(2-Sec. 11) Established the position for the corner on the Section line between Section corner K3 and the Meander corner on the East shore of Hagerman Lake (rec. L13, P168) at a position 1323.71' west of K3, the distance being 20.00 chains, proportionate to the original GLO record.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(9) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
6" Poplar N02°W 12.45' mrkd "1/16S BT"  
9" Sugar S58°E 10.45' do  
6" Maple S61°W 33.85' do  
7" Sugar N62°W 37.55' do  
Set sq'd cedar post adjacent.  
E= 7863237.023 N= 142448.235

(2) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
7" Sugar N11°W 2.15' mrkd "1/16S BT"  
10" Sugar S71°E 14.2' do  
11" Sugar S24°W 31.8' do  
9" Sugar N58°W 20.85' do  
Set sq'd cedar post adjacent.  
E= 7863255.652 N= 143249.475

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum.  
Coord. Ref.=NGS PID RL0456: N= 142561.037 m. E= 7864413.728 m.

Signed by Stephan J. Szyszkoski Date 07/13/2015  
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division