

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron Located In: Corner Code #
1. Public Land Survey
2. Property Controlling in Section
3. Miscellaneous Property in Sec.
4. Lot No. Recorded Plat
5. Private Claims

Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M) for Register of Deeds Stamp & File Number.

I, Stephan J. Szyszkoski, in a field survey on 04/23/15 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(SMC south of J4) Witness Corner to the Special Meander Corner (WCSMC) on the N-S 1/4 line of Sec. 11 at the north side of Bass Lake. Not established in the original survey.

(J4) Center of Section 11. Not previously monumented.



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(SMC) Established the position for the corner on the N-S 1/4 line of Section 11 at the north margin of the marsh bordering the north side of Bass Lake, 587.30' south of the Center of Section 11. The N-S 1/4 line is parallel with the line K4-K5.

(J4) Established the position on the E-W 1/4 line (by weighted mean bearing of the north Section line and that part of the south Section line lying east of Bass Lake) and at a distance from Quarter corner K4 that is twice that of K4 to 1/16 corner #9. The distance K4 to J4 is 2647.19'.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(SMC) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 5" W.Birch S57°E 9.6' Blazed and scribed 5" W.Birch S24°W 7.4' do 3" Balsam S56°W 4.5' do 7" Balsam N42°W 7.35' do Set sq'd cedar post adjacent. E= 7862830.702 N= 142283.770

(J4) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 3" Sugar S49°W 10.5' mrkd "C1/4 BT" 3" Sugar N49°E 10.8' do 3" Sugar S71°E 13.6' do 6" Sugar S27°E 23.0' do Set sq'd cedar post adjacent. E= 7862833.918 N= 142462.728

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum. Coord. Ref.=NGS PID RL0456: N= 142561.037 m. E= 7864413.728 m.

Signed by [Signature] Date 07/13/2015
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division