

# SURVEY & REMONUMENTATION

FEB 21 2001

## SECTION

### LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

COMMENCING YEAR 2000  
RECEIVED FOR RECORD  
IRON COUNTY, MICHIGAN

00 DEC 22 PM 3:25

L.C. Reggels: L. 8, P. 308

*Gary L. Pisoni*  
REGISTERED LAND SURVEYOR

Register of Deeds Stamp & File Number

For corners in

Iron  
(County)

Located In:

Corner Code #

1. Public Land Survey

T 43N R 31W

C.D-11w

T R

(005)

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

West Meander Corner Between Sections 29 and 32, T43N, R31W

I, Gary L. Pisoni, in a field survey on December 11, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established on July 16, 1849 by John Burt, U.S. Deputy Surveyor.

Original Corner; Wood Post

Original Bearing Trees:

White Pine	24"	S 15° E	11 links (7.26 feet)
White Pine	20"	N 67° W	53 links (34.98 feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No evidence of original B.T.s found.

Corner located on the West bank of the Michigamme River and is 28' from waters edge.

Restored the corner position by single proportionate measurement and set a witness corner meander corner on line between the Northwest Section corner and the North Quarter corner of Section 32.

Corner record research on file with County Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position, set a 5/8" diameter by 12" long rebar pin with a 3" diameter aluminum cap stamped as follows: Iron County Remonumentation, T43N, R31W, W.C.M.C., S- 29, S-32, N 89° 38'03"W, 0.97 feet, 2000, RLS 27457 from which I established the following new bearing trees: (all measurements taken to a nail in side of tree) No scribing, signs, or blazes

Cedar	14" (dbl)	N 26° W	45.75 feet
Balsam	7"	S 55° E	14.34 feet
Spruce	8"	S 71° W	14.63 feet
Steel sign post		N 70° W	0.55 feet


00-076

Signed by Gary L. Pisoni

Date 12-19-2000

Surveyor's Michigan License No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983  
REVISED OCT., 1995



LIBER

8 PAGE 308