

# SURVEY & REMONUMENTATION

FEB 21 2001

SECTION

COMMENCING YEAR 2000  
RECEIVED FOR RECORD  
IRON COUNTY, MICHIGAN

00 DEC -5 PM 12: 50

L.C. Records: L.8, P. 212

*Robert A. Goodreau*  
REGISTERED PROFESSIONAL SURVEYOR

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Iron Located In: Corner Code #  
(County)

1. Public Land Survey T 43N R 31W C-11  
T     R      
T     R      
T     R
2. Property Controlling S     T     R      
in Section S     T     R
3. Miscellaneous S     T     R      
Property in Sec. S     T     R

4. Lot No.       , Recorded Plat
5. Private Claims

I, Robert A. Goodreau in a field survey on March 20, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

C-11 Original corner established by John Burt, U.S. Deputy Surveyor, on 14 July 1849.

Original witnesses: Cedar 16" N86W 55 links  
Tamarack 18" S76E 34 links

Keith L. Sackett RLS restored corner on 12 March 1992 at found MI-WI Power Co. monument (Liber 6, Page 246).

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-11 Found Wisconsin Electric Power Co. monument.

Found witnesses recorded by Sackett as: 3" Spruce N 45° W 14.1' S30 NBT  
4" Spruce S 77° W 6.0' S31 NBT  
8" Cedar N 57° E 45.6' S29 NBT  
Old power pole missing

Corner record research on file with county representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-11 Accepted corner as found.

Witnesses: Accepted above bearing trees. S 47° E 18.15'  
Power pole (NEW) WEPCO #00-02365  
Sign post West 0.5'

Note: Measurements taken to a nail in side of witnesses.

Signed by *Robert A. Goodreau*  
Surveyor's Michigan License No. 43053

Date July 1, 2000

PEER GROUP APPROVED  
*Don Floyd, June 11-14, 2000*  
COUNTY REPRESENTATIVE

