

SURVEY & REMONUMENTATION

JAN 13 1998

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

IRON COUNTY
MICHIGAN
RECEIVED FOR RECORD

97 DEC 23 PM 1:29

L.C. Records 6.7 P. 155

Robert J. Pisoni
REGISTER OF DEEDS

For corners in

Iron
(County)

Located In:

Corner Code #

1. Public Land Survey

T 43N R 33W

E-11

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Section Corner Sections 28, 29, 32, 33, T43N, R33W

I, Gary L. Pisoni, in a field survey on November 25, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established in 1851 by Guy H. Carleton, U.S. Deputy Surveyor.
Original Corner; Wood Post

Original Bearing Trees;	Sugar	12"	S76°W	19 lks.(12.54 feet)
	Sugar	16"	N79° E	27 lks.(17.82 feet)

On 7-14-75, Arthur O. Enger, RLS with the Michigan Dept. Of Natural Resources, found a long standing fence corner presumed by common report to be the section corner. Enger set a 1"x36" iron pipe with a 3 1/2 " diameter aluminum cap. Recorded in Land Corner Certificate L.1, Page 502, on August 18, 1977.

1975 Corner References;	Sugar Maple	6"	N40°W	6.2 feet
	Sugar Maple	8"	S69° W	5.8 feet

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original corner evidence was recovered.

Found monument as set in 1975 by Arthur O. Enger, accept monument as best available evidence for restoring the corner position. Monument located at a fence corner running South and East and in line with the centerline of a county road running North.
1975 bearing tree;

Sugar Maple	9"	S76° W	6.18 feet
-------------	----	--------	-----------

Corner record research on file with County Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Blazed and scribed the following new bearing trees;(Measurements are taken to a nail in side of tree)

Sugar Maple	12"	N71° E	12.06 feet
Sugar Maple	13"	N03° E	18.62 feet
Steel Sign Post		North	0.90 feet

97-50
Signed by Gary L. Pisoni Date November 29, 1997

Surveyor's Michigan License No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1997

