

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Iron

(County)

Located in:

Corner Code #

1. Public Land Survey

T R
T R
T R
T R

2. Property Controlling
in Section

S T 43N R 33W 7a (MC N of E4)
S T 43N R 33W 14a (MC S of E4)

3. Miscellaneous
Property in Sec.

S T R
S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

14a Mar 27 2003

7a Mar 25 2003

I, Stephan J. Szyszkoski, in a field survey on _____, 20____ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7			8		9		10		11		12	
5													
6	18			17		16		15		14		13	
7													
8	19			20		21		22		23		24	
9													
10	30			29		28		27		26		25	
11													
12	31			32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

(7a) Meander corner between Sections 8 & 9, on the north bank of Chicaugon Creek. 1974: Reestablished by A.O.Enger, RLS "proportionately on line between Sec. Cor. 40.898 ch. S and 39.556 ch. N. Note: 1/4 cor. falls in creek on sec. line 44.3 ft. S of this corner". Set 1"IDx36" iron pipe with 3.5" aluminum cap. W.Spruce 14 N74W 52.9', Balsam 8 (on NW side of large boulder) S71E 22.4'

(14a) Meander Corner between Sections 8&9 on the south side of Chicaugon Creek. 1974: A.O.Enger RLS reestablished by proportionate measurement between section corners 41.158 ch. N and 39.296ch. S. 1/4 corner falls in creek on sec. line 61.5' N. of this corner. 1"IDx36" iron pipe with 3.5" aluminum cap. Tamarack 12 S22W 114.0', W.Spruce 12 S39E 103.4'.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(7a) Recovered the 1974 monument slightly disturbed, leaning to the south. The NBTs were not recovered. Measurements to corners south (MC and Sec. Cor.) and to north (Sec. Cor. reestablished by the undersigned) show that the top of the monument is now 0.37' south of the 1974 position, making it now 43.93' north of the unmonumented 1/4 corner. The monument was left in place, the ground being frozen. Made new witnesses as described below.

(14a) Found the 1974 monument in good condition and at record bearing and distance from the remaining NBT Tamarack SW in good condition. Checked distances to monuments north and south and found 41.166 ch. and 39.281 ch., respectively. Accepted a point 61.5' north of this position as the quarter corner E4 which I then used to control the subdivision of Section 8.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(7a) Found 1"ID Iron pipe with 3.5" dia.alum. State of MI cap. Blazed, scribed, and set measuring nails in:
8" Balsam N81W 27.35' "MC BT"
16" W.Pine N66W 61.1' (slope) do
4" Balsam N05W 30.6' do do
6" Balsam N39E 9.2' do do

Set squared cedar post adjacent. Bearings are magnetic. Distances are to nail with plastic tag.

(14a) Found 1"ID iron pipe with 3.5" aluminum State of MI cap. Blazed, scribed, and set measuring nails in:
4" Balsam S09W 88.3' "MC BT"
4" Balsam S18E 86.0' do
3" Balsam S34E 82.2' do
16" Tamarack S26W 114.0' (to notch)
The Tam. is the 1974 NBT with overgrown blazes. Bearings are magnetic. Distances to 2003 NBTs are to nail with tag.

Signed by Stephan J. Szyszkoski

Date 4/3/2003

Surveyor's Michigan License No. 33986

