

SURVEY & REMONUMENTATION

FEB 21 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

COMMENCING YEAR 2000
RECEIVED FOR RECORD
IRON COUNTY, MICHIGAN

00 DEC -5 PM 12: 51

L.C. Records: L. 8, P. 225

William A. Burt
PROFESSIONAL SURVEYOR

For corners in

Iron
(County)

Located In:

Corner Code #

1. Public Land Survey

T 43N R 36W

F-1

T 44N R 36W

F-13

T R

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, Robert A. Goodreau in a field survey on May 10, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

F-1/F-13 Original corner established by Austin Burt, U.S. Deputy Surveyor, in 1847.

Original witnesses: Yellow Birch 6" N 60° E 36 links
Sugar Maple 12" N 72° W 13 links

Donald D. Lappala RLS set 3/4" x 8" iron pipe on 23 September 1964 using 1934 Michigan State Highway project plans and reference monument. He also set a 2" x 5' concrete filled reference monument w/bronze tablet (Liber 3, Page 288).

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

F-1/F-13 Found PK nail in pavement set by unknown surveyor.

Found reference monument set by Lappala described as: North 39.3'

Found witnesses recorded by Lappala as: 7" Sugar Maple N 03° E 72.8' (110.3 links)
12" Yellow Birch N 19° E 85.4' (129.4 links)
3" Sugar Maple S 09°-30' W 71.3' (108.0 links)

Corner record research on file with county representative.

PEER GROUP APPROVED

Don D. Lappala 11-14-2000
COUNTY REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-1/F-13 Accepted corner as found.

Witnesses: 5" Maple S 12° W 71.70' (USFS BT sign)
8" Maple N 05° E 72.60' (USFS BT sign)
15" Y. Birch N 21° E 85.07' (USFS BT sign)
Mon. box N 06° E 7.38'
Sign post 1' South of reference monument.

Note: Measurements taken to a nail in side of witnesses.

Signed by R.A. Gohl
Surveyor's Michigan License No. 43053

Date July 1, 2000

