

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 4 T 44N R 32W	15
	S 4 T 44N R 32W	11
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3					4								
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 15 11/02/2011 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
Instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(15-Sec. 4) West 1/16 corner between Sections 4 and 9. Not previously monumented.

(11-Sec. 4) Southwest 1/16 corner. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(15-Sec. 4) Established the corner position midway and on the Section line between Section corner E3
1334.94' west and Quarter corner F3 1334.94' east.

(11-Sec. 4) Established the corner position at the intersection of straight lines connecting opposite
1/16 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(15) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
3" Sugar N19E 24.7' mrkd "1/16S BT"
10" Sugar S59E 12.85' do
4" W.Spruce S42W 13.1' do
9" Sugar N68W 22.5' do
Set sq'd cedar post adjacent.
Bearings are magnetic.

(11) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
3" Sugar S46E 10.6' mrkd " X X "
10" W.Spruce S15W 14.5' mrkd "1/16S BT"
10" W.Spruce N66W 12.5' do
5" Sugar N05W 10.2' do
Set sq'd cedar post adjacent.
Bearings are magnetic.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 01/11/2012

For the Michigan Department of Natural Resources, Forest Management Division

