

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 31 T 44N R 32W	9
	S T R	(GCDB 160140)
	S 31 T 44N R 32W	4
	S T R	(GCDB 120160)
	S T R	
3. Miscellaneous Property in Sec.		
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on 01/29/15 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(9-Sec. 31) Center-East 1/16 corner, Section 31. Not previously monumented.

(4-Sec. 31) Northwest 1/16 corner, Section 31. Not previously monumented.



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(9-Sec. 31) Established the position for the corner midway and on a straight line between Quarter corner 1321.42' east and the intersection of 1/4 lines of Section 31 1321.42' west.

(4-Sec. 31) Established the position for the corner at the intersection of straight lines connecting opposite 1/16 corners. The Center-West 1/16 corner position is proportionate to the dimensions derived from the information given on the original plat, it being 1318.65' west of the Center of Section 31 and 1290.30' east of the Quarter corner A12.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(9) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
5" Y.Birch N41°E 30.3' mrkd "1/16 S BT"
4" Blk. Ash S15°E 37.3' do
5" Cedar S61°W 45.6' do
11" Cedar N13°W 46.8' do
Set sq'd cedar post adjacent.
E= 7895611.602 N= 154673.783

(4) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
6" Balsam S77°E 11.15' mrkd "1/16S BT"
6" Maple in clump S24°E 15.45' do
10" Spruce S51°W 10.35' do
10" Maple N50°W 13.1' do
Set sq'd cedar post adjacent.
E= 7894813.509 N= 155086.438

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum.
Coord. Ref.=NGS PID AA8081: N= 147176.690 m. E= 7895147.466 m.

Signed by Stephan J. Szyszkoski Date 03/09/2015
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division