

LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Stephan J. Szyszkoski

Field Survey Date: See below

For corner(s) in: Iron County

Original Public Land Survey Corner

Corner Code

S T R  
S T R  
S T R  
S T R

Property Corner

1/16 Corner Code

a. S 14 T 44N R 32W  
a. S 23 T 44N R 32W  
b. S 15 T 44N R 32W  
S T R

15 (GCDB 520400)  
1 (GCDB 520400)  
13 (GCDB 460420)

|    |   |    |   |    |   |    |   |    |   |    |   |    |   |    |
|----|---|----|---|----|---|----|---|----|---|----|---|----|---|----|
| 1  | A | B  | C | D  | E | F  | G | H  | I | J  | K | L  | M | 1  |
| 2  |   | 6  |   | 5  |   | 4  |   | 3  |   | 2  |   | 1  |   | 2  |
| 3  |   |    |   |    |   |    |   |    |   |    |   |    |   | 3  |
| 4  |   | 7  |   | 8  |   | 9  |   | 10 |   | 11 |   | 12 |   | 4  |
| 5  |   |    |   |    |   |    |   |    |   |    |   |    |   | 5  |
| 6  |   | 18 |   | 17 |   | 16 |   | 15 |   | 14 |   | 13 |   | 6  |
| 7  |   |    |   |    |   |    |   |    |   |    |   |    |   | 7  |
| 8  |   | 19 |   | 20 |   | 21 |   | 22 |   | 23 |   | 24 |   | 8  |
| 9  |   |    |   |    |   |    |   |    |   |    |   |    |   | 9  |
| 10 |   | 30 |   | 29 |   | 28 |   | 27 |   | 26 |   | 25 |   | 10 |
| 11 |   |    |   |    |   |    |   |    |   |    |   |    |   | 11 |
| 12 |   | 31 |   | 32 |   | 33 |   | 34 |   | 35 |   | 36 |   | 12 |
| 13 | A | B  | C | D  | E | F  | G | H  | I | J  | K | L  | M | 13 |

Part A. Corner History

a. West 1/16 corner between Sections 14 and 23 T44N-R32W. Not previously monumented.

b. Southeast 1/16 corner, Section 15 T44N-R32W. Not previously monumented.



Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

a. May 2 2018. Established the position for the corner midway and on the Section line between Section corner 1311.87' west and Quarter corner 1311.87' east.

b. May 10 2018. Established the position for the corner at the intersection of straight lines connecting opposite 1/16 corners, those to the south and east being monumented.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

a. Set 1"IDx28" I.pipe with 2" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
14" Maple N67°E 8.6' mrkd "1/16S BT"  
7" Maple S67°E 12.8' do  
12" Maple S61°W 22.8' do  
8" Maple N31°W 21.0' do  
Set sq'd cedar post adjacent.  
E= 7901306.79 N= 158616.57

b. Set 1"IDx28" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
5" Tamarack N01°E 26.7' mrkd "1/16S BT"  
4" Tamarack N41°E 20.75' do  
11" Sugar S77°E 1.85' do  
14" Sugar S02°E 12.65' do  
Set sq'd cedar post adjacent.  
E= 7900510.85 N= 159034.43

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum.

Stephan J. Szyszkoski 05/30/2018