

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
	S 22 T 44N R 32W	H8
2. Property Controlling in Section	S 22 T 44N R 32W	5
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File  
Number

I, Stephan J. Szyszkoski, in a field survey on Dec. 12, 2007 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(H8) Center of Section 22. Not established in the original survey.

(5-Sec. 22) North 1/16 corner, Section 22. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(H8) Established the corner at the intersection of straight lines connecting opposite 1/4 corners. The Quarter corner between Sections 22 and 27 falls in the Michigamme Reservoir and its position was calculated midway and on line between Section corners G9 and I9.

(5-Sec. 22) Established the corner midway and on a straight line between Quarter corner 1312.49' north and Center of Section 1312.49' south.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(H8) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
5" Sugar N05E 15.8' mrkd "C1/4 BT"  
8" Sugar S82E 41.3' do  
10" Spruce S13W 27.8' do  
7" Y.Birch N49W 39.0' do  
Set sq'd cedar post adjacent. Bearings are magnetic.

(5) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
14" Sugar N26E 10.0' mrkd "1/16S BT"  
9" Sugar S44E 33.5' do  
10" Sugar S48W 15.0' do  
13" Sugar N38W 14.2' do  
Set sq'd cedar post adjacent. Bearings are magnetic.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													



Signed by Stephan J. Szyszkoski Date 12/12/07

Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Office of Land and Facilities

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS