

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____ T _____ R _____ T _____ R _____	_____
2. Property Controlling in Section	S 7 T 44N R 34W S _____ T _____ R _____ S 7 T 44N R 34W	SMC B3-B4 (GCDB 140556) 12
3. Miscellaneous Property in Sec.	S _____ T _____ R _____ S _____ T _____ R _____	(GCDB 140520)
4. Lot No. _____, Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on SMC 06/16/14
12 06/17/14 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(SMC B3-B4) Special Meander Corner on the N-S 1/4 line of Section 7, at the south shore of the
Paint River. Not previously monumented. This corner is common to Government Lots 5 (to west) and 6
(to east).

(12) Center-South 1/16 corner of Section 7. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(SMC B3-B4) Established the position for the corner at the Ordinary High Water Mark of the Paint
River at its intersection with the N-S 1/4 line of Section 7. The position for the corner was not
monumented. Established a Witness Corner on the 1/4 line approximately 17 feet south of the OHWM of
the river. The position for the Witness Corner is 1181.30' north of B4 and 1562.02' south of B3.

(12) Established the position for the corner midway and on a straight line between Quarter corner
1286.69' south and the Center of Section 7 1286.69' north.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(SMC) Set 1"IDx28" I.pipe with 2" alum. MDNR cap for
a Witness Corner approximately 17 feet south of the
corner position. Set measuring nail with MDNR tag
in the side of:
4" Cedar N11°E 12.7' mrkd "WC BT"
14" Cedar N80°E 25.7' do
9" Ash S25°E 53.8' do
18" Cedar S29°W 48.7' do
Set sq'd Cedar post adjacent.
E= 7876086.663 N= 161801.336

(12) Set 1"IDx32" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
14" Cedar N14°E 13.95' mrkd "1/16S BT"
12" Cedar N72°E 11.0' do
4" B.Ash S28°E 10.1' do
4" B.Ash N88°W 5.55' do
Set sq'd Cedar post adjacent.
E= 7876067.323 N= 161049.470

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum)
Coord. Ref.=NGS PID DI0209: N= 145460.522 m. E= 7873677.972 m.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 06/23/2014

For the Michigan Department of Natural Resources, Forest Resources Division

