

SURVEY & REMONUMENTATION

JAN 12 1996

COMMISSION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

IRON COUNTY
MICHIGAN
RECEIVED FOR RECORD

95 DEC 15 PM 2:22

L.C. Records L.C. P. 420

Gilbert Stobie
REGISTER OF DEEDS

For corners in

Iron

(County)

Located In:

Corner Code #

1

1. Public Land Survey

T44N R35W

K-6

T R

T R

T R

2. Property Controlling in Section

S

T R

S

T R

3. Miscellaneous Property in Sec.

S

T R

S

T R

4. Lot No. , Recorded Plat

5. Private Claims

Quarter Corner 13 & 14 T44N R35W

I, Gary L. Pisoni, in a field survey on October 23 19 95 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by Harvey Mellen, U.S. Deputy Surveyor on August 1851

Original corner: Wood Post

Original bearing trees:

Spruce

10"

N 8°E

28 links (18.48 feet)

White Pine

14"

S 81°E

40 links (26.40 feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

On October 1, 1969, Donald D. Lappala found remains of two original B.T.s and restored corner position at the record bearing and distance. Lappala marked corner position with a 2½" inside diameter by 5' long concrete filled iron pipe with a 3" circular bronze tablet.

ACT 74 Research on file with County Representative

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner

From the above described monument, I established the following new blazed and scribed bearing trees: (all measurements taken to a nail in side of tree)

Red Maple (NBT) 8"

N 40°W

21.70 feet

Sugar Maple(existing) 8"

S 56°E

13.50 feet

Sugar Maple(existing) 11"

S 30°W

27.07 feet

Red Maple (NBT) 10"

S 79°W

21.10 feet

Steel Sign Post

North

0.65 feet

Signed by

Gary L. Pisoni

Surveyor's Michigan License No.

27457

Date

11-30-95

PEER GROUP APPROVED

Gary L. Pisoni 12-14-95

COUNTY REPRESENTATIVE

