

LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Stephan J. Szyszkoski

Field Survey Date: 04/27/2016

For corner(s) in: Iron County

Original Public Land Survey Corner

Corner Code

S	T	R	
S	T	R	
S	T	R	
S	T	R	

Property Corner

1/16 Corner Code

a. S	14	T	45N	R	31W	10 (GCDB 500420)
a. S	15	T	45N	R	31W	14 (GCDB 500420)
b. S	14	T	45N	R	31W	11 (GCDB 520420)
S		T		R		

1	A	B	C	D	E	F	G	H	I	J	K	L	M	1
2		6		5		4		3		2		1		2
3														3
4		7		8		9		10		11		12		4
5														5
6		18		17		16		15		14		13		6
7														7
8		19		20		21		22		23		24		8
9														9
10		30		29		28		27		26		25		10
11														11
12		31		32		33		34		35		36		12
13	A	B	C	D	E	F	G	H	I	J	K	L	M	13

Part A. Corner History

a.) South 1/16 corner between Sections 14 and 15. 1980 - Established by K.L.Sackett RLS midway and on line between corners I06 and I07. Set 1"IDx36" iron pipe with 4" aluminum cap. 6" Spruce S47°W 18.1', 3" Spruce N05°E 22.7'.

b.) Southwest 1/16 corner, Section 14. Not previously monumented.

Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

a.) Found the 1980 monument in good condition and at record bearing and distance from the 1980 witness 3" Spruce (now 9") NE, in good condition with overgrown blazes. The monument is substantially midway and on line between I06 and I07 and I accept same as a careful and faithful establishment of the position of the corner.

b.) Established the position for the corner at the intersection of straight lines connecting opposite 1/16 corners, those to the south and west being monumented.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

(a.) Found 1"ID I.pipe with 4" alum. MDNR cap. Set measuring nail with MDNR tag in the side of:
 9" Spruce N13°E 22.95' old blazes (1980 BT)
 7" Cherry S77°E 23.95' mrkd "1/16S BT"
 3" Cherry S10°E 14.7' do
 6" Spruce S67°W 25.8' do
 Set sq'd cedar post adjacent.
 E= 7910718.445 N= 168469.390

(b.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of:
 6" Spruce N34°E 9.35' mrkd "1/16S BT"
 8" Poplar S03°W 23.7' do
 11" Spruce S78°W 14.05' do
 6" Spruce N45°W 13.5' do
 Set sq'd cedar post adjacent.
 E= 7911118.930 N= 168458.675

Bearings are magnetic. Coordinates are MCS83, NAD83(2011) Epoch 2010.00, in meters.
 Coordinate Reference: NGS PID RL0202, E= 7917031.357 m. N= 156159.387 m.

Stephan J. Szyszkoski 08/23/2016

Professional Surveyor's License No.: 33986

page 1 of 1

Prepared By: S.J. Szyszkoski for the Michigan Dept. of Natural Resources, 427 N. US41 Baraga, MI 49908

