

LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Stephan J. Szyszkoski

Field Survey Date: 04/26/2016

For corner(s) in: Iron County

Original Public Land Survey Corner

Corner Code

S T R
S T R
S T R
S T R

Property Corner

1/16 Corner Code

a. S 11 T 45N R 31W 16 (GCDB 560500)
a. S 14 T 45N R 31W 2 (GCDB 560500)
b. S 14 T 45N R 31W 6 (GCDB 560460)
S T R

1	A	B	C	D	E	F	G	H	I	J	K	L	M	1
2		6		5		4		3		2		1		2
3														3
4		7		8		9		10		11		12		4
5														5
6		18		17		16		15		14		13		6
7														7
8		19		20		21		22		23		24		8
9														9
10		30		29		28		27		26		25		10
11														11
12		31		32		33		34		35		36		12
13														13
	A	B	C	D	E	F	G	H	I	J	K	L	M	

Part A. Corner History

a.) East 1/16 corner between Sections 11 and 14. 1980 - Established by K.L.Sackett RLS midway and on line between Section and 1/4 corners. Set 1"IDx36" Iron pipe with 3-1/2" alum. Cap. 9" Spruce S52°E 98.8', 7" Spruce S16°W 77.5'.

b.) Northeast 1/16 corner, Section 14. Not previously monumented.

Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

a.) Found the 1980 monument in good condition and at record bearing and distance from the remaining 1980 witness 7" (now 9") Spruce SW. The monument is substantially midway and on a straight line between corners J5 and K5 and I accept same as a careful and faithful establishment of the position of the corner.

b.) Established the position for the corner at the intersection of straight lines connecting opposite 1/16 corners, those to the north and east being monumented.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

(a.) Found 1"ID I.pipe with 3-1/2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of:
9" Spruce S19°W 77.65' old blazes (1980 BT)
6" Poplar S81°E 56.7' mrkd "1/16S BT"
6" Poplar S58°E 61.8' do
7" Poplar S01°W 62.0' do
Existing Cedar post adjacent.
E= 7911944.096 N= 169658.731

(b.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of:
5" B.Spruce N19°E 6.85' mrkd "1/16S BT"
8" B.Spruce S68°E 18.5' do
5" B.Spruce S07°W 17.55' do
6" Balsam S79°W 21.25' do
Set sq'd cedar post adjacent.
E= 7911935.977 N= 169249.120

Bearings are magnetic. Coordinates are MCS83, NAD83(2011) Epoch 2010.00, in meters.
Coordinate Reference: NGS PID RL0202, E= 7917031.357 m. N= 156159.387 m.

Stephan J. Szyszkoski

08/23/2016

Professional Surveyor's License No.: 33986

page 1 of 1

Prepared By: S.J. Szyszkoski for the Michigan Dept. of Natural Resources, 427 N. US41 Baraga, MI 49908

