

LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Stephan J. Szyszkoski

Field Survey Date: 06/01/2016

For corner(s) in: Iron County

Original Public Land Survey Corner

a. S T 45N R 31W
 S T R
 S T R
 S T R

Corner Code

H09 (GCDB 440300)

Property Corner

b. S 21 T 45N R 31W
 b. S 22 T 45N R 31W
 S T R
 S T R

1/16 Corner Code

14 (GCDB 400320)
 10 (GCDB 400320)

1	A	B	C	D	E	F	G	H	I	J	K	L	M	1
2		6		5		4		3		2		1		2
3														3
4		7		8		9		10		11		12		4
5														5
6		18		17		16		15		14		13		6
7														7
8		19		20		21		22		23		24		8
9														9
10		30		29		28		27		26		25		10
11														11
12		31		32		33		34		35		36		12
13	A	B	C	D	E	F	G	H	I	J	K	L	M	13

Part A: Corner History

a.) Quarter corner common to Sections 22 and 27. 1849 - Established by John Burt, Deputy, midway and on line between Section corners 40.00 chains east and west. Set cedar post. Cedar 8" S42°E 8 links, Sugar 16" N65°W 7 links. In 2010, David E. Erickson PS worked in this area and computed a position for this corner proportionate to the original record, but it was not monumented at that time.

b.) South 1/16 corner between Sections 21 and 22. Not previously monumented.

Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

a.) The original post and accessories were not recovered. Found no evidence of the position of the original corner on the ground. Reestablished the position for the corner midway and on the Section line between Section corners G09 2635.45' west and I09 2635.45' east, being proportionate to the original record. From the corner thus reestablished, a Celotex location poster with signatures dating to 1958 was found affixed to a 9" Sugar Maple N80°E, 2.4' distant.

b.) Established the position for the corner midway and on the Section line between Section corner 1314.15' south and Quarter corner 1314.15' north.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

a.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
 Set measuring nail with MDNR tag in the side of:
 4" Sugar North 30.95' mrkd "1/4S NBT"
 9" Sugar N80°E 2.4' do
 5" Sugar S73°W 6.4' do
 10" Sugar N75°W 8.9' do
 Set sq'd cedar post adjacent.
 E= 7909866.845 N= 166492.322

b.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
 Set measuring nail with MDNR tag in the side of:
 5" Ironwood N07°E 3.9' mrkd "1/16S BT"
 4" Poplar S79°E 12.8' do
 5" Poplar S31°E 8.0' do
 3" Poplar N39°W 15.25' do
 Set sq'd cedar post adjacent.
 E= 7909070.126 N= 166911.395

Bearings are magnetic. Coordinates are MCS83, NAD83(2011) Epoch 2010.00, in meters.
 Coordinate Reference: NGS PID RL0202, E= 7917031.357 m. N= 156159.387 m.

Stephan J. Szyszkoski

08/23/2016

Professional Surveyor's License No.: 33986

page 1 of 1

Prepared By: S.J. Szyszkoski for the Michigan Dept. of Natural Resources, 427 N. US41 Baraga, MI 49908

