

LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Stephan J. Szyszkoski

Field Survey Date: February 2, 2017

For corner(s) in: Iron County

Original Public Land Survey Corner

Corner Code

S T R
S T R
S T R
S T R

Property Corner

1/16 Corner Code

S 21 T 45N R 37W
S 22 T 45N R 37W
S T R
S T R

14 (GCDB 400320)
10 (GCDB 400320)

1	A	B	C	D	E	F	G	H	I	J	K	L	M	1
2		6		5		4		3		2		1		2
3														3
4		7		8		9		10		11		12		4
5														5
6		18		17		16		15		14		13		6
7														7
8		19		20		21		22		23		24		8
9														9
10		30		29		28		27		26		25		10
11														11
12		31		32		33		34		35		36		12
13	A	B	C	D	E	F	G	H	I	J	K	L	M	13

Part A. Corner History

South 1/16 corner between Sections 21 and 22. Not previously monumented.

Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

Established the position for the corner midway and on the Section line between Quarter corner 1320.35' north and Section corner 1320.35' south. The observed true bearing of the line between said corners is S 00°10'54"E.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
10" Maple N06°W 7.55' mrkd "1/16S BT"
8" Maple S31°E 11.65' do
6" B.Spruce S20°W 14.25' do
5" Y.Birch S82°W 7.05' do
Set sq'd cedar post adjacent.

Bearings are magnetic.



Stephan J. Szyszkoski

02/02/2017

Professional Surveyor's License No.: 33986

page 1 of 1

Prepared By: S.J. Szyszkoski for the Michigan Dept. of Natural Resources, 427 N. US41 Baraga, MI 49908