

SURVEY & REMONUMENTATION

FEB 21 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

	Iron (County)	Located In:	Corner Code #
1. Public Land Survey	T 44N R 37W	B-1	
	T 45N R 37W	B-13	
	T R		
	T R		
2. Property Controlling in Section	S T R		
	S T R		
3. Miscellaneous Property in Sec.	S T R		
	S T R		

COMMENCING YEAR 2000
RECEIVED FOR RECORD
IRON COUNTY, MICHIGAN

00 DEC -8 PM 1:05

L.C. Records: L.S., P. 266

Robert J. Pisoni
REGISTERED LAND SURVEYOR

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

Quarter Corner to Section 31, T45N, R37W
Quarter Corner to Section 6, T44N, R37W

I, Gary L. Pisoni, in a field survey on October 18, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established on June 9, 1847 by John Burt, U.S. Deputy Surveyor.
Original Corner; Sugar Post
Original Bearing Trees:

Sugar	18"	N 20°E	22 links (14.52 feet)
Yellow Birch	24"	N 52° W	30 links (19.80 feet)

In 1946, G. A. Shadko, RLS restored the corner position with a 4" diameter concrete monument with a brass cap stamped as follows: Michigan Conservation Department, Public Fishing Site, T45N, R37W, 1/4, S-31, S-6, T44N, 1946, G.A.Shadko.

In 1982, John H. Fisher, RLS recovered the above monument and established the following new bearing trees:

Sugar Maple	10"	S 35°W	2.51 feet
Hemlock	7"	N 25°W	45.25 feet
Hemlock	11"	N 51°E	31.45 feet
Steel sign post		N 61°W	2.15 feet

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No evidence of original B.T.s found.

Found monument as described above and the following bearing trees:

Hemlock	16"	N 37° E	31.40 feet
Sugar Maple	16"	S 29° W	2.44 feet
Hemlock	9"	N 31° W	45.24 feet
Steel sign post		N 65° W	2.2 feet

Monument is 6" above ground surface.

Corner record research on file with County Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Blazed and scribed the following new bearing tree: (All measurements taken to a nail in side of tree)

Sugar Maple	8"	N 78° W	29.99 feet
-------------	----	---------	------------

00-034

Signed by Gary L. Pisoni Date 11-13-2000

Surveyor's Michigan License No. 27457

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 29, 1971

