LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

| lron (County) | _ Located In: | Corner Code # | |
|--|---|---|--|
| 1. Public Land Survey | T 46N R 33V | (GCDB 200300) | 5,9 |
| 2. Property Controlling in Section | T 46N R 33N S T R S T R S T R | (GCDB 300440) | |
| 3. Miscellaneous Property in Sec. | S T R | | |
| 4. Lot No. , Red 5. Private Claims | corded Plat | | Register of Deeds Stamp & File Number 1 A B C D E F G H I J K L M |
| above were in conformance with r instructions of the United States I a Court of Law and /or that the c | 74, Michigan P.A. of 1970, the corregulations and rules therefore as a Department of the Interior, Bureau orner points mentioned in lines 3, I of Land Surveyors or by a De | 03/12/15 03/23/15 do hereby state briner points mentioned in lines 1 and 2 required in the current manual of survey of Land Management or by a decree of 4 and 5 above were in conformance with ecree of a Court of Law; established, | 7 |
| | ered, round as expressed below: | range, may be recorded | 9 10 30 29 28 27 26 25 11 12 31 32 33 34 35 36 |

- A. Description of original monument and accessories and/or subsequent restoration:
- (C9) Corner common to Sections 19-20-29-30. 1977 Corner remonumented by A.O.Enger RLS at the position of a found Northern Paper Mills monument which had been set at record bearing and distance from the original BTs in 1953. Set 1" IDx36" I.pipe with 3 3/4" alum. cap. Sugar Maple 5" N65°E 13.1', Sugar Maple 7" S45°E 34.2'.
- (E6) Quarter corner common to Sections 16 and 17. 1953 record of S.R. Wickman and N.J.Peryam of Northern Paper Mills Forestry Division state: Orig. B.T.s Tam 8 N40°E 4; Tam. 8 S35°W 31; 12/24/35 B.G.Buell and Seppala found Tam. 8 N40°E 4 dry stub face plain, Tam 8 S35°W 31 broken stub I.M.; 12/29/49 D.Buell and Peryam found Tam 8 N40°E 4 dry stub I.M. faint; 3/12/53 S.Wickman & Peryam found Tam 8 N40°E 4 dry stub I.M. faint, old weasel marks and Reg's. Set pipe [& brass cap] from Tam. B.T. Spruce 6 S73°E 22, Spruce 6 N43°E 26.
- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
- (C9) Found the 1977 monument in good condition and at record bearing and distance from the 1977 accessories, both in good condition with overgrown blazes. Accepted the monument as a careful and faithful perpetuation of the position of the original corner.
- (E6) Found the 1953 NPM capped pipe, in good condition, at record bearing and distance from the 1953 NBTs. The Spruce SE is a 2' tall rotting stump with face, the Spruce NE is a rotted stump. Accepted the monument as a careful and faithful perpetuation of the position of the original corner.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

| (C9) Found 1"ID I.pipe with 3 3/4" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 9" Sugar N70°E 13.1' old blazes (1977 NBT) 10" Sugar S45°E 34.6' do do 12" Y.Birch N45°W 39.5' mrkd "S19 NBT" 6" Sugar N17°W 28.9' do E= 7886840.103 N= 176550.648 | (E6) Found 1"ID I.pipe with brass NPM cap. Set measuring nail with MDNR tag in the si 5" B.Spruce N14°E 16.0' mrkd "1/4S 5" B.Spruce S45°E 26.1' do 5" Tamarack S57°W 18.6' do 5" Tamarack N68°W 17.3' do Set sq'd spruce post adjacent. E= 7888490.565 N= 178926.966 | de of NBT" |
|--|---|---------------|
|--|---|---------------|

| Bearings are magnetic. Coordinates are M | MCS83 in meters, 1 | NAD83 (2011) Epoch | 2010.00 datum | |
|--|--------------------|--------------------|---------------|---|
| Coord. Ref.=NGS PID RL0476: N | V= 196482.411 m. | E= 7879234.516 m. | 0.5 14 | |
| AAN () | , | | C. A. | - |
| signed by Stephen & maylest. | Date | 08/06/2015 | * STEPHAN J. | Y |
| Surveyor's Michigan License No. 3398 | B6 | | SZYSZKOSKI | 7 |
| Franklin Michigan B | _ | | a LAND | |

For the Michigan Department of Natural Resources, Forest Resources Division

PROFESSIONARS SOCIODES JAN. 725 1971

REVERSIONARS SOCIETA SOC

FORM APPROVED BY MICHIGAN STATE BOARD OF