

LAND CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
(Iron Co.)	46 34	E1, F1
1. PUBLIC LAND SURVEY	T. 47 N. 34 W.	E13, F13
(Iron Co.)	4 46 34	2
2. PROPERTY CONTROLLING IN SECTION	33 T. 47 N. 34 W.	16
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. E. S. R. W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on March 2, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

- A. Description of original monument and accessories and/or subsequent restoration:
- Corner E13: This corner re-established from original bearing trees by Northern Paper Mills
- Corner F13: Original monument and accessories not found.
- Corner 16: Not set on original survey or subsequently apparently.

- B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:
- Corner E13: Found 1" I.D. by unknown length Iron Pipe with 2" brass cap by Northern Paper Mills.
- Corner F13: Re-established on line between corners east and west.
- Corner 16: Established on line between section corner east and $\frac{1}{4}$ corner west.

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
- | | |
|--|--|
| Corner E13: 1" I.D.xUnknown length Iron Pipe with 2" brass cap
8" Cedar N1E 6.9 ft. S33, NBT
10" Cedar N89W 18.2 ft. S32, NBT
9" Cedar S1W 25.9 ft. S5, NBT | Corner 16: Set 1" I.D.x40" Iron Pipe with 4" aluminum cap
6" Sugar N62E 10.7 ft. 1/16S, BT
12" Sugar S62W 17.5 ft. 1/16S, BT
8" Sugar N39W 28.5 ft. 1/16S, BT |
| Corner F13: Set 1" I.D.x36" Iron Pipe with 4" aluminum cap
4" Balsam S43W 7.7 ft. $\frac{1}{4}$ S, NBT
9" Balsam N1W 25.0 ft. $\frac{1}{4}$ S, NBT
7" Spruce N57E 23.5 ft. $\frac{1}{4}$ S, NBT | |

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)


FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE July 1, 1978

CHIEF OF SURVEY PARTY
MICHIGAN REGISTERED LAND SURVEYOR
Keith L. Sackett
Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006



FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REPEALED MAY 14, 1978

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET