

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron Located In: Corner Code #
1. Public Land Survey
2. Property Controlling in Section
3. Miscellaneous Property in Sec.
4. Lot No. , Recorded Plat
5. Private Claims

Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M) for Register of Deeds Stamp & File Number.

I, Stephan J. Szyszkoski, in a field survey on 01/27/16 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(K8-8, Sec. 24) A point on the E-W 1/4 line of Section 24 between Quarter corner K8 and the Center-West 1/16 corner, Section 24 (#8). Not previously monumented.

(3-4, Sec. 24) A point on the North 1/16 line of Section 24 between 1/16 corners #3 and #4. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(K8-8, Sec. 24) Established the position for the corner on the E-W 1/4 line of Section 24 237.00' east of Quarter corner K8 and 1076.95' west of 1/16 corner #8, Section 24.

(3-4, Sec. 24) Established the position for the corner on the North 1/16 line of Section 24 727.00' east of 1/16 corner #3 and 589.86' west of the unmonumented position for 1/16 corner #4 (intersection of 1/16 lines).

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(K8-8) Set 1"IDx28" I.pipe with 2" alum. MDNR cap stamped POL C-C Sec 24. Set measuring nail with MDNR tag in the side of: 5" W.Birch N28°W 11.05' mrkd "POL BT" 3" Balsam S70°E 5.5' do 3" Balsam S01°W 16.55' do 4" Cherry S75°W 17.05' do Set sq'd cedar post adjacent. E= 7883724.699 N= 177424.381

(3-4) Set 1"IDx28" I.pipe with 2" alum. MDNR cap stamped POL N-N Sec 24. Set measuring nail with MDNR tag in the side of: 5" Balsam N37°W 8.9' mrkd "POL BT" 5" Balsam N70°E 11.0' do 7" Cedar S45°E 17.3' do 14" Cedar S20°W 15.7' do Set sq'd cedar post adjacent. E= 7883882.077 N= 177823.299

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum. Coord. Ref.=NGS PID RL0476: N= 196482.409 m. E= 7879234.515 m.

Signed by [Signature] Date 02/17/2016
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division