

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Iron  
(County)

Located In:

Corner Code #

1. Public Land Survey

T 46N R 34W 88

T R

T R

S T R

2. Property Controlling  
in Section

S 19 T 46N R 34W 11

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

11 Jul 24 2005

88 Jul 21 2005

I, Stephan J. Szyszkoski, in a field survey on \_\_\_\_\_, 20\_\_\_\_ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(88) Center of Section 19. Not established in the original survey. Found no subsequent record.

(11-Sec. 19) Southwest 1/16 corner, Section 19. Not established in the original survey. Found no subsequent record.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(88) Established the corner at the intersection of straight lines connecting opposite 1/4 corners. From the position thus established, I found a 1/2" dia. rebar projecting about 2.0', N14W 1.6' distant, which I did not accept for the corner.

(11-Sec. 19) Established the corner at the intersection of straight lines connecting opposite 1/16 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner

(88) Set 1"IDx32" I.pipe with 4" alum.

MDNR cap. Set measuring nails in:

4" Sugar S50E 14.8' mrkd "C1/4 BT"

12" W.Pine S31W 11.6' do

12" Sugar N70W 25.6' do

21" W.Pine N08W 11.0' do

Set sq'd cedar post adjacent. Bearings are magnetic. Distances are to nail with tag.

(11) Set 1"IDx32" I.pipe with 4" alum.

MDNR cap. Set measuring nails in:

5" Cedar N28W 70.9' mrkd "1/16S BT"

6" Cedar S30E 13.3' do

10" Cedar S65W 40.8' do

3" Cedar N09W 10.1' do

Set sq'd cedar post adjacent. Bearings are magnetic. Distances are to nail with tag.



Signed by

Stephan J. Szyszkoski

Surveyor's Michigan License No.

33986

Date

8/25/05

For the Michigan Department of Natural Resources, Office of Land and Facilities

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971  
Revised May 14, 1975  
Revised Jan., 1983  
Revised Oct., 1995