

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

MARY O'L ZOOG

For corners in				
KALKASKA	Located In:	Corner Code #	S	ECTION
(County) 1999 REMONUMENTATION 1. Public Land Survey	T <u>25N</u> R <u>7W</u> TR TR			. 2020452
2. Property Controlling in Section S 3. Miscellaneous S Property in Sec. S	TR TR TR TR	Kalkaska County J	oan Hall, Register Register of Deeds	3020152 Page: 1 of 1 02/04/2000 03:40P REMON LB: 6 PG: 98 Stamp & File Number
4. Lot No, Recorded	Plat			
5. Private Claims			A B C D E F  2 6 5 4  3 4 7 8 9	G H I J K L I
I, FUGENE FARRIER, in that under requirements of P.A. 74, Mand 2 above were in conformance with management or by a decree of a Courand 5 above were in conformance with Decree of a Court of Law; established below:	fichigen P.A. of 1970, the rith regulations and rules to United States Departme t of Law and for that the o th the rules of the Michiga	corner points mentioned in lines 1 therefore as required in the current int of the Interior, Bureau of Land orner points mentioned in lines 3, 4 an Board of Land Surveyors or by a	8 19 20 21	22 23 24
NOTE: Not more than 2 comers, all on this certificate.	in the same town and rang	e, may be recorded	11 12 31 32 33	39 35 36
A. Description of original monum G-7: Sec. Cor. Common to Sec. 1, 1853, G.L.O. Resurvey, by V.W. Cauk 20 Lks; Sugar 20", N29°E, 14 Lks 1914, Survey, by W.S. Merrill (Co. Su 1972, Survey & LCRC, by J.L. Witcox road, raised with 1/2" iron; \$20°W, 260.82'; \$60°W, 20" Twin Maple told 1993, Survey, by E. Farrier (Co. Surve 1997, Survey, by Farrier Surveying, fo \$50°E, 36" Maple, 29.90'; set nail \$200.	7.18.19. & 20. T25N-in (Deputy Surveyor) Co. Survey Bk 34, (LCRC recorded in Liber 14", W. Pine, 93.28'; S57° wit) 84.6' yor), found 1/2" iron rod 8 und iron & caps in centerlin	R7W. Garfield Township Survey Notes Pg 20, set post comer, Pg 87-88, found old stake with stor , Pg 4} found 2" rod 2' deep in cent W, corner fence post, 45.08'; S47° c cap S20°W, 20" Pine, 93.28'; S4' e road intersection (Birgy & Hensche	ne on West eide terline road to North & 2' N E, 22" Maple, 29.63'; 525 1°E, 22" Maple, 29.63'; 52 all Rds) set nail N28°E, pov	orth of centerline of E-W °W, 20" Maple (old wit) 25°W, 20" Maple, 60.82
B. Description of comer evidence fou C-7: Sec. Cor. Common to Sec. 17. Found 1/2" iron & cap #14102 2' Eas N28°E, 66.05', power pole, found nai S50°E, 29.90', 36" Maple, found nail S28°W, 64.33', 13" W. Pine, found r S53°W, 44.80', telephone post w/rise No G.L.O. witnesses were found.	t of centerlina of N-S road  leil ar, found nail P.A.3  Chair	ed by Peer Group  45 - 1990 Kalkaska County	* EU F/ PRO: SI	GENE D. ARRIER FESSIONAL REVEYOR NO. 24594 ESSIONAL REVEYOR RE
C. Description of monument for corr C-7: Sec. Cor. Common to Sec. 1' Found 1/2" iron & cap #14102 2' Eas N28°E, 66.05', power pole, found nail \$50°E, 29.90', 36" Maple, found nail \$28°W, 64.33', 13" W. Pine, found r \$53°W, 44.80', telephone post w/rise Kalkaska County Peer Group accepted	7, 18, 19, & 20, T25N-t of centerline of N-S road it in the second in th	and in centerline E-W road. Pulled &	tion of the corner: . set 5/8" X 18" rerod w/br.	ass cap.

Signed by August Michigan License No. 24594

\_Surveyor's

Date 07-04-00