

For corners in

Kalkaska
(County)

Located In:

Corner Code #

- | | T 25N R 7W | | K-2 |
|---------------------------------------|------------|---|-----|
| 1. Public Land Survey | T | R | |
| 2. Property Controlling
in Section | S | T | R |
| 3. Miscellaneous
Property in Sec. | S | T | R |

4. Lot No. _____, Recorded Plat _____

5. Private Claims

I, Craig W. McVean, in a field survey on Feb. 24, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

K-2 - GLO - Set 1/4 post. Tho. Whelpley - 1853

Hemlock 30" N48 3/4°E 5 L.

Hemlock 10" N62 3/4°W 29 L.

- Fargo Eng. - B.L. Caulkin - 1912 - Fnd. stk. & 2 Hem. stp's. per U.S. - set iron & crockery mon.
- Rec. Survey L3 P. 102 - E. Farrier - 1987 - Fnd 1" pipe per Fargo in N-S fence line.
 - N5°W 31.60' 7" Cedar
 - S35°E 15.23' 6" Balsam
 - N37°E 5.84' 8" Balsam
 - N50°W 19.32' 10" Balsam

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-2 - 1/4 Corner common to Sec. 1 & Sec. 2, T25N, R7W- Fnd. P.S. cap #24594 (EF) in 1" O.D. x 2.3' iron pipe with hook foot end per Fargo Eng. Also, fnd. 1" x 7" long cedar stake at base of pipe. No crockery found. Fargo pipe accepted as a careful and faithful perpetuation of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-2 - Replaced Fargo pipe w/ 4" DNR Alum. cap on 1" x 36" galv. iron pipe.- Reset stake on N. side at base pipe.

- * N7°W 31.70' to set N&T in E. Side 8" Cedar (EF)
 - * N53°W 19.50' to set N&T in NE Side 11" B. Fir (EF)
 - * S41°E 15.24' to set N&T in SE Side 8" B. Fir (EF)
 - S8°W 74.78' to set N&T in E. Side 9" Cedar - scribed 'XBT'
 - S56°W 70.88' to set N&T in NE Side 7" Cedar - scribed 'XBT'
- Set Blue Carsonite post 1' SE - Fnd. 4" Cedar post NE 0.85' to face.

* EDF wit nails above.

Signed by Craig W. McVee
Surveyor's Michigan License No. 39088

Date 12/9/1999

