



8023272

Tx:4016447

11/29/2012 1:00:00 PM

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

DOCUMENT #

3111414

JOANN DEGRAAF

KALKASKA CTY ROD

KALKASKA, MI

RECORDED ON

11/29/2012 1:31 PM

REC FEE: 14.00

PAGES: 1

BK: 3PG: 338

For Corners In:

Kalkaska

(County)

Located In

Corner Code #

1. Public Land Survey

T 26N R 6W F9

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Section

S T R

4. Lot No:

Recorded Plat:

5. Private Claims:

I, Joshua R. Davidson, in a field survey on August 8, 2012 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

F9 - 1852 - GLO - G. Cannon - set 1/4 sec. post

1) Cedar 12" S26°E 25

2) Cedar 14" N20°W 9

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

F9 - 1/4 Corner common to sections 21, & 28, T26N, R6W. Searched calculated area for GLO evidence. Area had been logged and disturbed by equipment. Found stumps of cedars that had been cut in the area, but could not fit two together to determine GLO position. Set a 4" DNR aluminum cap on a 1" X 36" galvanized iron pipe by single proportion between section corners E9 and G9. DNR monument accepted as a careful and faithful reestablishment of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F9 - Set stamped 4" DNR aluminum cap on 1" X 36" galvanized iron pipe.

N75°E 42.79' to set nail & tag in N. side 4" R. Maple scribed "XBT"

S56°E 27.18' to set nail & tag in SW. side 6" Ash

S18°W 20.44' to set nail & tag in W. side 3" R. Maple

N10°W 50.74' to set nail & tag in E. side 5" Ash

Set blue carsonite post 1' West

Signed by:

Joshua R. Davidson

Date:

11-29-2012

Surveyor's Michigan License No.:

46659