



8 0 2 3 2 7 5
Tx:4016447

11/29/2012 1:00:00 PM

85

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Kalkaska
(County)

Located In

Corner Code #

1. Public Land Survey	T	26N	R	6W	H8		
	T		R				
2. Property Controlling in Section	S	22	T	26N	R	6W	8
	S		T		R		
3. Miscellaneous Property in Section	S		T		R		
	S		T		R		

4. Lot No: _____ Recorded Plat: _____

5. Private Claims: _____

I, Joshua R. Davidson, in a field survey on February 28, 2011 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

H8 - none

8. none



B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

H8 - Center 1/4 corner section 22. Set stamped 2" Aluminum cap On 5/8" x 34" rebar at intersection of 1/4 lines per standard BLM procedure.

8 - CW 1/16 corner Section 22. Set stamped 2" Aluminum cap on 5/8" x 34" rebar per standard BLM procedure.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H8 - Set a stamped 2" Aluminum Cap on 5/8" x 34" rebar.

8 - Set a stamped 2" Aluminum Cap on 5/8" x 34" rebar.

N26°E 66.35' to set nail & tag in NW. side 17" Red Maple
S72°E 21.84' to set nail & tag in N. side 10" Jack Pine
S77°W 63.76' to set nail & tag in S. side 10" White Pine
N42°W 34.17' to set nail & tag in NE. side 8" Fir
Set blue Carsonite post with location tag 1' southeast

S87°E 18.23' to set nail & tag in N. side 2" Red Maple
S32°E 59.88' to set nail & tag in W. side 16" Red Maple
S50°W 31.48' to set nail & tag in SE. side 3" Red Maple
N48°W 13.35' to set nail & tag in NE. side 13" Cherry
Set blue Carsonite post with location tag 1' southwest

Signed by:

Joshua R. Davidson
Surveyor's Michigan License No.: 46659

Date:

11-29-2012