

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

KALKASKA
(County)

Located In:

Corner Code #

2000 REMONUMENTATION

1. Public Land Survey

T.27N R.6W

1-6

T. R.

T. R.

T. R.

2. Property Controlling
in Section

S. T. R.

S. T. R.

3. Miscellaneous
Property in Sec.

S. T. R.

S. T. R.

4. Lot No. , Recorded Plat

5. Private Claims

I, EUGENE FARRIER, in a field survey on September 7, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1-6: 1/4 Cor. Common to Secs. 14 & 15, T27N-R6W, Excelsior Township

1852: GLO resurvey by G. H. Cannon; set post for corner; Hemlock 33", S 74°E, 44 links;

Beech 6", N 30°W, 28 links.

1895: Survey by E.B. Dinnis, (Co. Surveyor); found stake

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1-6: 1/4 Cor. Common to Secs. 14 & 15, T27N-R6W, Excelsior Township

Set 5/8" iron with brass single pin between found Section corners, corner is 1' West Baker Road N-S and 10' North of trail road West.
No G.L.O. witnesses were found.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1-6: 1/4 Cor. Common to Secs. 14 & 15, T27N-R6W, Excelsior Township

Set 5/8" iron with brass single pin between found Section corners, corner is 1' West Baker Road N-S and 10' North of trail road West.

N 45°E, 42.65', 5" Maple, set nail and tag

S 34°E, 39.36', 7" Maple, set nail and tag

S 66°W, 51.81', 10" Red Pine, set nail and tag

N 42°W, 51.05', 20" Cherry, set nail and tag

Kalkaska County Peer Group accepted the above monument as a careful and faithful reestablishment of the position of the original corner.

Ratified by Peer Group

P.A. 345-1990 Kalkaska County

Chairman Eugene Farrier

Date 2-14-01

Signed by Eugene Farrier

Surveyor's Michigan License No. 24594

Date 2-15-01



Kalkaska County Joan Hall, Register

3026846

Page: 1 of 1

02/18/2001 10:28

REMON

LB: 6 PG: 175

SURVEY &
REMONUMENTATION

FEB 26 2001

SECTION

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

