

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

KALKASKA

(County)

2000 REMONUMENTATION

1. Public Land Survey

Located In:

Corner Code #

T 27N R 6W

1-7

T R

T R

T R

T R

T R

T R

T R

2. Property Controlling
In Section

S

T R

3. Miscellaneous

S

T R

Property in Sec.

S

T R

SURVEY &
REMONUMENTATION

FEB 26 2001

SECTION

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, EUGENE FARRIER, in a field survey on September 7, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
1-7: Section Corner Common to Sections 14, 15, 22, & 23, T27N-R6W

1852: GLO resurvey by G.H. Cannon; set post for corner; Hemlock 10", N 33°W, 10 links; Sugar 18", S 65°20 E, 6 links.

1973: LCRC by Norm F. Parker (not recorded); set 1/2" bar for corner by proportionate distance N & S; evidence of fences and occupation set corner at 5297' from NW corner; Blaze 8", N. Pine, N 36°W, 66.71'; 12" Maple, S 50°W, 34.69'; 15" Cherry, N 48°E, 53.48'; 12" Cherry, S 88°E, 26.45'.
1999: Survey by D.E. Schripserma (not recorded); found spike; 10" Maple, S 24°W, 52.66'; 18" Cherry, S 89°E, 27.40'; 18" Cherry, N 44°E, 54.22'; 12" R. Pine, N 29°E, 63.03'.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
1-7: Section Corner Common to Sections 14, 15, 22, & 23, T27N-R6W

Found spike 1' West centerline Baker Road N-S 6' South centerline Wagenschutz Road.
No GLO witnesses were found.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
1-7: Section Corner Common to Sections 14, 15, 22, & 23, T27N-R6W

Found spike 1' West centerline Baker Road N-S 6' South centerline Wagenschutz Road. Set 5/8" rebar with brass cap.
N 25°E, 63.04', 12" Red Pine, found spike
N 53°E, 54.20', 18" Cherry, set nail and tag
S 83°E, 27.40', 12" Maple, set nail and tag
S 38°E, 35.69', 10" Maple, set nail and tag
S 54°W, 35.27', 14" Maple, set nail and tag

Kalkaska County Peer Group accepted the above monument as a careful and faithful reestablishment of the position of the original corner.

Ratified by Peer Group

P.A. 345 - 1990 Kalkaska County


Chairman Eugene Farrier

Date 2-14-01

Signed by Eugene Farrier

Surveyor's License No. 24594

Date 2-15-01



3026847

Page: 1 of 1

82/18/2001 10:26A

REMON

LB: 6 PG: 178

APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1976
REVISED JAN., 1983
REVISED OCT., 1996