37	00
	distribute a distribute
4.7	5

expressed below:

FEB 1 4 1997

"other code

For corners in		OMIVIDATION Filing Require	R RECORDATION CERT ement of Act 74, Mich. P UNTY REMONUMENTATI	P.A. 1970 # 6 5 6 2	
	Kent	Located in: Caledonia	Corner Code #		
	(County)	Township		S A A S S S S S S S S S S S S S S S S S	
1.	Public Land Survey	T R T R T R		REEDS REEDS	
_	D	T R	NAT- A NATA- A - A	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
2.	Property Controlling in Section	S <u>2</u> T <u>5N</u> R <u>10W</u> S <u>T</u> R <u> </u>	West Witness Monument	9550	
3.	Miscellaneous	S R	629.9' West of K-3	· ·	
	Property in Sec.	S T R		Register of Deeds Stamp & File Number	
4.	Lot No	, Recorded Plat			
5.				A B C D E F G H I J K I	
		, '		2 5 5 4 5	:
	·	* * *		3	Ļ
	Bandy Kolehouse	in a field survey on Aug	ust 19 19	96 4 7 8 9 10 11 11	2

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration:

do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the comer points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as

K-3C 183	1 G.L.O. Notes	Mullett	Corner Falls in Lak	e - Set Temporary Point
192	6 Survey "Keiser Park Pla	t" McNutt	N/A	
198	1983 L.C.R.C. #6722 T. Chettleburgh Fnd. Iron Pipe in Monumer		lonument Box / Set K.C. Monument	
199	5" L.C.R.C. #8134	K. Breitels	K.C. Monument	P.A. 345 1990 KENT COUNTY
				PEER APPROVED 8/22/96
				ON ACCOUNT TO A COLUMN

This corner was originally approved by the Kent County Remonumentation Peer Group and mໍລານັກຄໍລາໄຂຢ bỳ on1/14/93 and was recorded per L.C.R.C. #6720.

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-3C Found a Standard Kent County 52' M/L West of the West shore of Campau Lake per L.C.R.C.'s #6722 and #8134 as set by T. Chettleburgh in place of a 1" iron pipe he found per Keiser Park Plat. Monument is 7.12' South and 629.9' West of K-3 (in lake).

L.C.R.C. #6722

L.C.R.C. #8134

Nail/Tag S side 15" Cottonwood S 79° E 28.85' Nail/Tag W side 32" Cottonwood S 25° W 80.32' West Shoreline Campau Lake East 52.00' +/-Nail/Tag NW side 28" Cottonwood S 40° W 23.36' Nail/Tag SW side 32" Cottonwood

Nail & KC Remon, tag S. side 18" Cottonwood S 79° E 28.90' (m. 28.86') Nail & KC Remon. tag W. side 32" Cottonwood S 25° W 80.34' (m. 80.22') Nail & KC Remon. tag NW side 28" Cottonwood S 40° W 23.41' (m. 23.35') Nail & KC Remon, tag N, side Tw. 22" Cottonwood N 88° W 93.17' (m. 93.00') Nail/Tag N side Twin 19" Cottonwood N 88° W 93.14' Nail & KC Remon. tag SW side 36" Cottonwood N 55° W 32.39' (m. 32.37') West shoreline Campau Lake - East 52' m/l

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

Description of manument for corner and accessories established to pernet

K-3C Standard Kent County Monument

Nail & K.C. remon. tag on S side 15" Cottonwood S 79° E 28.86'

Nail & K.C. remon. tag on W side 38" Willow S 25° W 80.22'

Nail & K.C. remon. tag on NW side 32" Willow S 40° W 23.35'

Nail & K.C. remon. tag on N side Twin 24" Cottonwood N 88° W 93.00'

25854

Nail & K.C. remon. tag on SW side 32" Willow N 55° W 32.37

West shoreline Campau Lake - East 52' m/l

Signed by /EXATH TECH

OF MICHIG RANDY J. KOLEHOUSE LAND SURVEYOR 25854 ENSED LAND

REVISED JAN., 1983

Surveyor's Michigan License No.