

\$7.00  
\$2.00 SEP 18 1995  
COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
KENT COUNTY REMONUMENTATION

Kent  
(County)

Located in:

Corner Code #

1. Public Land Survey  
T 5N R 12W A-4  
T      R            
T      R            
T      R
2. Property Controlling  
in Section S      T      R       
S      T      R
3. Miscellaneous  
Property in Sec. S      T      R       
S      T      R

4. Lot No.     , Recorded Plat
5. Private Claims

REG. OF DEEDS

8547

Register of Deeds Stamp & File Number

STATE OF MICHIGAN  
COUNTY OF KENT  
RECEIVED FOR RECORD  
95 AUG 28 AM 10:46

I, Randy Kolehhouse, in a field survey on March 13 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A-4 This corner was not originally set by the G.L.O.

1975	L.C.R.C. #962	Exxel Engineering	"T" Iron
1981	L.C.R.C. #1551	Nederveld & Jonker	Fnd. "T" Iron/Set K.C. Monument
1988	L.C.R.C. #4626	Olson, Meyers & May	K.C. Monument
1990	L.C.R.C. #5702-A	J. Bueche	K.C. Monument

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Nederveld & Jonker on 1/28/81 and was recorded per L.C.R.C. #1551.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-4 Found standard Kent County Monument on the C/L of Kenowa Avenue per L.C.R.C.'s #1551, #4626 and #5702-A as set by Jack Bueche in place of a broken K.C. Monument set by Nederveld & Jonker. Said monument was set in place of a "T" iron they found which checked L.C.R.C. #962.

L.C.R.C. #962

Nail in sde dbl 18" Ash NE 25.75'  
Iron South 155.8'

L.C.R.C. #1551

Nail & Remon. tag on S side 24" W. Cherry E 27.72'  
Nail & Remon. tag on NE side 10" Apple SSE 54.33'  
Nail & Remon. tag on E side 10" dbl. Ash NNE 26.04'  
Ottawa County Corner S 155.87'

L.C.R.C. #5702-A

Nail & remon. tag NE side 10" Apple S 25° E 54.22'  
Nail & remon. tag S side 26" Cherry S 87° E 27.72'  
Sq. spk. in E side 14" Ash S 10° W 158.56'

P.A. 345 1990 KENT COUNTY

PEER APPROVED 5/25/99

CHAIRMAN

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-4 Standard Kent County Monument

Nail & K.C. remon. tag on NE side 10" Apple S 25° E 54.15'  
Nail & K.C. remon. tag on S side 26" Cherry S 87° E 27.75'  
Nail & K.C. remon. tag on SW side 6" Maple N 53° W 53.05'  
O.C. Monument S 155.85'

Signed by Randy J. Kolehhouse  
EARTH TECH

Date 8/2/95

Surveyor's Michigan License No. 25854

