

\$7.00
\$2.00

SEP 18 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
KENT COUNTY REMONUMENTATION

For corners in

Kent
(County)

Located in:

Corner Code #

- | | | | | | |
|------------------------------------|---|----|---|-----|-----|
| 1. Public Land Survey | T | 5N | R | 12W | A-5 |
| | T | | R | | |
| | T | | R | | |
| | T | | R | | |
| 2. Property Controlling in Section | S | | T | R | |
| | S | | T | R | |
| 3. Miscellaneous Property in Sec. | S | | T | R | |
| | S | | T | R | |

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randy Kolehhouse, in a field survey on March 13 19 95, do hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A-5	1817	G.L.O. Notes	L. Lyon	Set Post
	1975	L.C.R.C. #962	Exxel Engineering	3/4" Iron
	1981	L.C.R.C. #1552	Nederveld & Jonker	Fnd. 3/4" Iron/Set K.C. Monument
	1988	L.C.R.C. #4627	Olson, Meyers & May	K.C. Monument
	1990	L.C.R.C. #5703-A	J. Bueche	K.C. Monument

P.A. 395-1000 KENT COUNTY

PEER APPROVED 5/25/95
CHAIRMAN Randy Kolehhouse

This corner was originally approved by the Kent County Remonumentation Peer Group and monumented by Nederveld & Jonker on 1/30/81 and was recorded per L.C.R.C. #1552.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-5 Found standard Kent County Monument on Town line 8' M/L West of the C/L of Kenowa Avenue running N-S and 1' M/L South of the C/L of 76th Street running East as set by Nederveld & Jonker in place of a 3/4" iron they found which checked L.C.R.C. #962.

L.C.R.C. #1552

L.C.R.C. #5703-A

Nail & Remon. tag on SE side P. pole NE 77.12'
"X" on W end culv. SSW 34.58'
Ottawa County corner S 164.88'

Nail & remon. tag SE side PP N 55° E 77.14'
Nail & remon. tag SE side PP S 53° W 44.49'
Pk in NE side PP S 30° E 50.46'
"X" cut on W end conc. culvert S 30° W 34.58'
"X" cut on E end conc. culvert S 25° E 65.89'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-5 Standard Kent County Monument on Town Line

"X" in end culv. SSW 34.62'
Nail & K.C. remon. tag on SE side P. pole N 55° E 77.20'
Nail & K.C. remon. tag on SE side P. pole S 53° W 44.38'
Nail & K.C. remon. tag on NE side P. pole S 30° E 50.42
"X" cut in E end conc. culv. S 25° E 65.89'
Closing corner 0.36' West (not set)
Ottawa County mon. South 164.88'

Signed by Randy J. Kolehhouse

Date 8/21/95

Surveyor's Michigan License No. 25854

